

# Paintworks Specification CDS 210.6 CF

<b>System</b>	<b>SOLAGARD® Low Sheen</b>	APAS 0280/3&5
<b>Substrate</b>	<b>Exterior – James Hardie’s Scyon Stria™, Scyon Linea™, Scyon PrimeLine® cladding systems</b>	
<b>Category</b>	<b>Ultra Premium – Water Based</b>	

## Product Features

Wattyl SOLAGARD® Low Sheen is a premium quality, water based, 100% acrylic paint with exceptional resistance to the effects of sun and weather. Designed to be applied to most exterior surfaces without the use of a primer. James Hardie’s Scyon Stria™, Scyon Linea™, PrimeLine® weatherboard is an attractive pre-primed range of claddings systems manufactured from fibre cement. Wattyl SOLAGARD® Low Sheen offers a 15 year paint warranty against flaking, peeling or blistering when used in conjunction with James Hardie’s Scyon Stria™, Scyon Linea™ or PrimeLine® weatherboard. For full terms and conditions of the warranty and registration details please refer to Wattyl’s website at [www.wattyl.com.au/specifiers/AR/jameshardiescyon.htm](http://www.wattyl.com.au/specifiers/AR/jameshardiescyon.htm) or phone Wattyl Customer Service on 132101.

## Surface Preparation

Installation of the cladding system must be carried out as per James Hardie’s installation recommendations. James Hardie’s Scyon Stria™, Scyon Linea™, PrimeLine® claddings systems must be coated within 3 months once exposed to exterior weathering. There must be less than 15% moisture in the surface at the time of application to ensure optimum coating performance. The surface must be free from dirt, grease, oil, mould, release agents, and other contaminants that may interfere with adhesion. Repair imperfections with a suitable exterior grade filling compound.

Application Details	Data Sheet	Coverage M <sup>2</sup> /L	Film Thickness (microns)		Dry Times	
			Wet	Dry	Touch	Recoat
First Coat: <b>SOLAGARD® Low Sheen</b> (equipment: brush, roller or spray)	D4.14	16 M <sup>2</sup> /L	63	24	30 minutes	2 hours
Second Coat: <b>SOLAGARD® Low Sheen</b> (equipment: brush, roller or spray)	D4.14	16 M <sup>2</sup> /L	63	24	30 minutes	2 hours

## Recommended Uses

For exterior use only.  
For use on suitably prepared exterior timber, masonry, brick, fibre cement sheet\*, cement render, PVC (downpipes) and previously painted surfaces. \*Excludes monolithic fibre cement sheet cladding where joints are taped and set.

## Additional Notes

INFORMATION HOTLINE Ph: 132101. For additional installation information, warranties and warnings in regards to the James Hardie’s Scyon Stria™, Scyon Linea™, PrimeLine® cladding systems refer to [www.jameshardie.com.au](http://www.jameshardie.com.au) or ask James Hardie on 131103. The Paint Warranty Registration Form can be either downloaded from Wattyl’s website at [www.wattyl.com.au/specifiers/AR/jameshardiescyon.htm](http://www.wattyl.com.au/specifiers/AR/jameshardiescyon.htm) or is available by phoning Wattyl Customer Service on 132101. Completed Paint Warranty Registration Forms must be mailed to Wattyl Technical Services, P.O. Box 6464 Blacktown, NSW 2148, within thirty (30) days of the original application of Solagard® paint to the subject premises. Surface preparation is the responsibility of the Builder, Renovator or Main Contractor and the Applicator. To achieve the indicated performance, it must be carried out in accordance with Wattyl’s recommendations.

## Caution

Provide adequate ventilation during use.  
Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

- This information is provided with respect to the listed Wattyl products. Wattyl recommends that: (a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
- The information in this specification sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.
- Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.
- To the full extent permitted by law, Wattyl’s liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl’s election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.