

WATTYL DECK AND EXTERIOR TIMBER CLEANER

Chemwatch Material Safety Data Sheet
Issue Date: Wed 31-Aug-2005

CHEMWATCH 5131-95
CD 2005/2 Page 2 of 12
Section 2 - HAZARDS IDENTIFICATION

Wear suitable protective clothing.
To clean the floor and all objects contaminated by this material, use water.
Take off immediately all contaminated clothing.
In case of accident or if you feel unwell IMMEDIATELY contact Doctor or Poisons Information Centre (show label if possible).

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
oxalic acid	144-62-7	1-10
anionic surfactants		<1
water	7732-18-5	>60

Section 4 - FIRST AID MEASURES

SWALLOWED

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

EYE

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
- Immediately flush body and clothes with large amounts of water, using safety shower if available.
 - Quickly remove all contaminated clothing, including footwear.
 - Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
 - Transport to hospital, or doctor.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed,

continued...

WATTYL DECK AND EXTERIOR TIMBER CLEANER

Chemwatch Material Safety Data Sheet

Issue Date: Wed 31-Aug-2005

CHEMWATCH 5131-95

CD 2005/2 Page 3 of 12

Section 4 - FIRST AID MEASURES

where possible, prior to initiating first aid procedures.

- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

Treat symptomatically.

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

INGESTION:

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjunctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

continued...

WATTYL DECK AND EXTERIOR TIMBER CLEANER

Chemwatch Material Safety Data Sheet
Issue Date: Wed 31-Aug-2005

CHEMWATCH 5131-95
CD 2005/2 Page 4 of 12
Section 5 - FIRE FIGHTING MEASURES

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
 - Wear full body protective clothing with breathing apparatus.
 - Prevent, by any means available, spillage from entering drains or water course.
 - Use fire fighting procedures suitable for surrounding area.
 - Do not approach containers suspected to be hot.
 - Cool fire exposed containers with water spray from a protected location.
 - If safe to do so, remove containers from path of fire.
 - Equipment should be thoroughly decontaminated after use.
- When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 800 metres in all directions.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.
- Expansion or decomposition on heating may lead to violent rupture of containers.
- Decomposes on heating and may produce toxic/ irritating fumes.
- May emit acrid smoke.
- Non combustible.
- Not considered to be a significant fire risk.
- Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).
- May emit acrid smoke. May emit corrosive fumes.

FIRE INCOMPATIBILITY

Avoid reaction with oxidising agents.

HAZCHEM

2X

Personal Protective Equipment

PERSONAL PROTECTION EQUIPMENT

Breathing apparatus.

Gas tight chemical resistant suit.

Limit exposure duration to 1 BA set - 30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

continued...

WATTYL DECK AND EXTERIOR TIMBER CLEANER


Chemwatch Material Safety Data Sheet
Issue Date: Wed 31-Aug-2005

CHEMWATCH 5131-95
CD 2005/2 Page 5 of 12
Section 6 - ACCIDENTAL RELEASE MEASURES

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

PROTECTIVE ACTIONS FOR SPILL



From IERG (Canada/Australia)

Isolation Distance	25 metres
Downwind Protection Distance	250 metres
IERG Number	36

FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.
- 3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.
- 4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also

continued...

WATTYL DECK AND EXTERIOR TIMBER CLEANER

Chemwatch Material Safety Data Sheet
Issue Date: Wed 31-Aug-2005

CHEMWATCH 5131-95
CD 2005/2 Page 6 of 12

Section 6 - ACCIDENTAL RELEASE MEASURES

considered "small spills".

LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.

- 5 Guide 153 is taken from the US DOT emergency response guide book.
- 6 IERG information is derived from CANUTEC - Transport Canada.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

oxalic acid	500 mg/m ³
water	500 mg/m ³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

oxalic acid	5 mg/m ³
water	500 mg/m ³

other than mild, transient adverse effects

without perceiving a clearly defined odour is:

oxalic acid	2 mg/m ³
water	500 mg/m ³

The threshold concentration below which most people

will experience no appreciable risk of health effects:

oxalic acid	1 mg/m ³
water	500 mg/m ³

American Industrial Hygiene Association (AIHA)

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - Use in a well-ventilated area.
 - Avoid contact with moisture.
 - Avoid contact with incompatible materials.
 - When handling, DO NOT eat, drink or smoke.
 - Keep containers securely sealed when not in use.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately. Launder contaminated clothing before re-use.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
- DO NOT allow clothing wet with material to stay in contact with skin.

continued...

WATTYL DECK AND EXTERIOR TIMBER CLEANER

Chemwatch Material Safety Data Sheet
Issue Date: Wed 31-Aug-2005

CHEMWATCH 5131-95
CD 2005/2 Page 7 of 12
Section 7 - HANDLING AND STORAGE

SUITABLE CONTAINER

- Lined metal can, Lined metal pail/ can
 - Plastic pail
 - Polyliner drum
 - Packing as recommended by manufacturer.
 - Check all containers are clearly labelled and free from leaks.
- For low viscosity materials
- Drums and jerricans must be of the non-removable head type.
 - Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):
- Removable head packaging;
 - Cans with friction closures and
 - low pressure tubes and cartridges may be used.
 -
 - Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.
alkalies.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³
--------	----------	------------	--------------------------	-------------	---------------------------	-------------	---------------------------

Australian Exposure
Standards

Oxalic acid

1

2

No data available for water as (CAS: 7732-18-5)

Not available. Refer to individual constituents.

INGREDIENT DATA

OXALIC ACID:

There is only scant data regarding the toxicology of industrial exposure to airborne oxalates. There is no data regarding potential systemic toxicity or bioavailability of inhaled oxalates. The TLV-TWA (corresponding to 0.27 ppm on a molecular basis) is comparable to that of sulfuric acid and phosphoric acid and is thought to provide protection against the risk of eye and skin burns and respiratory tract irritation.

continued...

WATTYL DECK AND EXTERIOR TIMBER CLEANER

Chemwatch Material Safety Data Sheet
Issue Date: Wed 31-Aug-2005

CHEMWATCH 5131-95
CD 2005/2 Page 8 of 12

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

The recommendation for a STEL is added to prevent irritation of skin and mucous membranes.

WATER:

No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION

EYE

- Chemical goggles.
- Full face shield.
- Contact lenses pose a special hazard; soft contact lenses may absorb irritants and all lenses concentrate them.

HANDS/FEET

Elbow length PVC gloves.
When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.
An approved self contained breathing apparatus (SCBA) may be required in some situations.
Provide adequate ventilation in warehouse or closed storage area.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear green liquid with a mild odour; mixes with water.

PHYSICAL PROPERTIES

Mixes with water.

Corrosive.

Acid.

Molecular Weight: Not Applicable
Melting Range (°C): Not Available
Solubility in water (g/L): Miscible
pH (1% solution): Not Available

Boiling Range (°C): 80-100
Specific Gravity (water=1): 1.03
pH (as supplied): 1.3
Vapour Pressure (kPa): Not Available

continued...

WATTYL DECK AND EXTERIOR TIMBER CLEANER

Chemwatch Material Safety Data Sheet
Issue Date: Wed 31-Aug-2005

CHEMWATCH 5131-95
CD 2005/2 Page 9 of 12

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Volatile Component (%vol): 85 approx	Evaporation Rate: Not Available
Relative Vapour Density (air=1): 1	Flash Point (°C): Not Applicable
Lower Explosive Limit (%): Not Available	Upper Explosive Limit (%): Not Available
Autoignition Temp (°C): Not Available	Decomposition Temp (°C): Not Available
State: LIQUID	

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
-

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

The material can produce severe chemical burns within the oral cavity and gastrointestinal tract following ingestion.

EYE

The material can produce severe chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating.

When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.

SKIN

Skin contact with the material may be harmful; systemic effects may result following absorption.

The material can produce severe chemical burns following direct contact with the skin.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

Not normally a hazard due to non-volatile nature of product.

Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly

continued...

WATTYL DECK AND EXTERIOR TIMBER CLEANER

Chemwatch Material Safety Data Sheet
Issue Date: Wed 31-Aug-2005

CHEMWATCH 5131-95
CD 2005/2 Page 10 of 12
Section 11 - TOXICOLOGICAL INFORMATION

derived from the vascular system.

Acidic corrosives produce respiratory tract irritation with coughing, choking and mucous membrane damage. Symptoms of exposure may include dizziness, headache, nausea and weakness. In more severe exposures, pulmonary oedema may be evident either immediately or after a latent period of 5-72 hours. Symptoms of pulmonary oedema include a tightness in the chest, dyspnoea, frothy sputum and cyanosis. Examination may reveal hypotension, a weak and rapid pulse and moist rates. Death, due to anoxia, may occur several hours after onset of the pulmonary oedema.

The material is not thought to produce adverse health effects following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

CHRONIC HEALTH EFFECTS

Repeated or prolonged exposure to acids may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucous production.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.
unless otherwise specified data extracted from RTECS - Register of Toxic Effects
of Chemical Substances

OXALIC ACID:

Not available. Refer to individual constituents.

WATER:

No significant acute toxicological data identified in literature search.

continued...

WATTYL DECK AND EXTERIOR TIMBER CLEANER

Chemwatch Material Safety Data Sheet
Issue Date: Wed 31-Aug-2005

CHEMWATCH 5131-95
CD 2005/2 Page 11 of 12

Section 12 - ECOLOGICAL INFORMATION

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

OXALIC ACID:

Daphnia magna EC50 (48hr.) (mg/l): 25

Algae IC50 (72hr.) (mg/l): 80-790

log Pow (Verschuereen 1983): 1.88372093

BOD5: 0.1

BOD20: 0.115

COD: 0.18

ThOD: 0.18

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

log Kow : -0.81- -0.43

BOD 5 if unstated: 0.086-0.14

COD : 0.126-0.18

ThOD : 0.18

Toxicity Fish: TLm(24)4000mg/L

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

log Kow : -0.81- -0.43

BOD 5 if unstated: 0.086-0.14

COD : 0.126-0.18

ThOD : 0.18

Toxicity Fish: TLm(24)4000mg/L

Section 13 - DISPOSAL CONSIDERATIONS

Puncture containers to prevent re-use and bury at an authorised landfill.

- Recycle wherever possible.

- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

- Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material).

- Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION

Shipping Name:

CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

Dangerous Goods Class: 8

continued...

WATTYL DECK AND EXTERIOR TIMBER CLEANER

Chemwatch Material Safety Data Sheet
Issue Date: Wed 31-Aug-2005

CHEMWATCH 5131-95
CD 2005/2 Page 12 of 12

Section 14 - TRANSPORTATION INFORMATION

Subrisk: None
UN/NA Number: 3265
Packing Group: III
Labels Required: corrosive
Additional Shipping Information:
International Transport Regulations:
IMO Dangerous Goods class: 3265
IMO Packing group: II
IATA Dangerous goods class: 8
Cargo Instructions: 820
Cargo Max: 60 L
Passenger Instructions: 818
Passenger Max: 5 L
Special Provisions: None, 274

HAZCHEM

2X

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

S6

REGULATIONS

oxalic acid (CAS: 144-62-7) is found on the following regulatory lists:
Australian Inventory of Chemical Substances (AICS)
Australian Poisons Schedule

water (CAS: 7732-18-5) is found on the following regulatory lists:
Australian Inventory of Chemical Substances (AICS)

Section 16 - OTHER INFORMATION

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Wed 31-Aug-2005
Print Date: Wed 31-Aug-2005