

SOLAGARD® DIY Bagged Finish

Page 1 of 2
Resource Code: 114521
December 2009

DESCRIPTION

- Watty SOLAGARD® DIY Bagged Finish is a premixed polymer render designed to provide a bagged or rendered finish, depending on application technique. Use Solagard DIY Bagged Finish as part of your bag and paint system on garden walls, retaining walls, and outdoor feature walls. Solagard DIY Bagged Finish is designed to be topcoated with Solagard Masonry Matt or any other Solagard Finish.

PRINCIPAL CHARACTERISTICS

- Solagard DIY Bagged Finish is supplied pre-mixed ready for use.
- Easy application with a lambs wool mitt. Multiple coats of Solagard DIY Bagged Finish may be applied to provide a more uniform finish on uneven surfaces or raked brickwork.
- Solagard DIY Bagged Finish can be finished with a plastic trowel to give a rendered finish.
- Outstanding durability when topcoated with Solagard paint finishes.

COLOURS AND GLOSS

- Off-White
- Matt, coarse texture

BASIC DATA

- **Surface Dry** Four (4) hours.
- **Recoat** Twenty four (24) hours.
- **Topcoat** Twenty four (24) hours.
All figures are quoted at 25°C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat** up to 1.0 M²/L (depending on the surface uniformity, porosity, and method of finishing).
- **Wet Film Thickness** 1000 microns (approx)
- **Dry Film Thickness** 650 microns (approx)
- **Clean-up** Thoroughly clean equipment with water away from drains.

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- Solagard DIY Bagged Finish is suitable for use on unpainted and painted exterior rigid substrates such as cement render, brick, masonry, fibre cement, Autoclaved Aerated Concrete (AAC). Note: Not suitable for Monolithic Fibre Cement as joints will crack.
- Not suitable for walk on surfaces, porous or terracotta pots.
- Ensure the surface is clean and dry. All loose, peeling and flaking material must be removed prior to coating.
- Apply Solagard DIY Bagged Finish direct to correctly prepared bare surfaces.
- For previously painted surfaces, ensure the surface is in sound condition by removing loose, peeling or flaking material with a scraper. Sand the surface smooth and remove all dust.
- To test paint soundness, cut a small X in the paint with a sharp blade. Stick a piece of tape firmly over the X and pull off. If the paint pulls away, the surface is unsound. Repeat at random in a number of areas. Unsound surfaces should be stripped for best results.
- Sand any enamel paint until gloss is removed.
- Apply one coat of Solagard Low Sheen White as a key coat to all previously painted surfaces to ensure adhesion of Solagard DIY Bagged Finish.
- Fill large holes with a suitable exterior filler and sand lightly to an even finish.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.
- Any mould spots must be treated with bleach, and then rinsed with clean water before painting.
- New cement or render must be completely cured (usually 8 weeks) before application.
- Due to possible variability in tilt-up and pre-cast concrete surfaces, contact the Watty Hotline phone number 132 101 to determine the most suitable method of preparing these substrates prior to painting.

INSTRUCTIONS FOR USE

- Stir contents thoroughly before use.
- Use of a drop sheet is highly recommended.
- Due to the nature of Solagard DIY Bagged Finish, the end finish will depend on the application and finishing methods used.
- Generally only one coat is required on relatively uniform surfaces. Two coats may be required on raked brickwork and other non-uniform surfaces; particularly if a smooth, rendered finish is to be achieved.
- Practicing the application technique on a board or unseen area is recommended before attempting large jobs.

First Coat

- For all finishes, apply using a sheepskin mitt. Scoop product onto the mitt and spread over the wall using a random or sweeping motion. Work in sections across the wall. This will create a finish similar to cement bagging.
- Keep hands flat to avoid drag marks.
- Rotate mitt to prevent uneven wearing.
- To minimise spillage, avoid over loading the mitt.
- Apply no more than 2mm thickness per coat.

Alternative Application: Rendered Finish

- Apply with mitt as above.
- For a smoother finish, use a plastic trowel to smooth the finish once it has tacked off (approx 10-15 min). Take care not to remove the coating. Finish in a small circular motion for a very smooth finish, or larger sweeping strokes for a less uniform effect.
- For a brushed-style finish, lightly brush over the coating whilst still wet.

Second Coat (if required)

- Apply and finish as per first coat.

Topcoats

- Apply two coats of Solagard Masonry Matt in your choice of colour.
- For a different effect, topcoat with Solagard Stone Finish.

SAFETY DATA

- **Caution** Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers.
- **M.S.D.S.:** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid:**
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

ADDITIONAL DATA

- Available in 10 litre containers.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- For further information, contact the Wattyl Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that:
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.

3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.

4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

