



DESCRIPTION

- a penetrating fast drying sealer primarily for use on timber floors

PRINCIPAL CHARACTERISTICS

- fast drying and easy sanding
- excellent adhesion
- suitable sealer for WattyI Estapol 7008, Estapol SP Gloss and Estapol Tung Oil systems

Note: We advise that you must test this product to determine if it is suitable for your particular use.

COLOUR AND GLOSS

- clear

BASIC DATA AT 25° C and 50% RELATIVE HUMIDITY

- touch-dry 15 minutes
- recoat 20 minutes
- practical spreading rate 10 m²/L, depending on the surface porosity
- shelf life (cool, dry place) at least 12 months in unopened container

SURFACE PREPARATION

- all surfaces must be free from wax, silicone, oil and other contaminants
- fill nail holes or cracks with WattyI Woodstop Timber Putty in a matching colour (do not use linseed oil putty). Allow to dry for at least 30 minutes, then fine-sand using equipment and paper appropriate to the flooring material
- do not over-sand
- if required, stain with WattyI Floor Stain (11692-LINE). Direct staining with dye-based stains is not recommended

INSTRUCTIONS FOR USE

- **NOT FOR SPRAY APPLICATION!**
- agitate thoroughly with a flat-bladed stirrer before and during use

Timber Floors:

- thinning not usually required however if necessary thin with up to 10% WattyI T10 Thinner
- use a WattyI applicator pad or mohair roller
- finish with suitable WattyI floor finish
- clean up with WattyI T35 Thinner

IMPORTANT NOTES REGARDING THE COATING OF TIMBER FLOORS:

- use conventional coating techniques, being prepared to re-sand and re-coat if an adhesion problem arises. (Lack of adhesion is caused by the waxes and oils that may be present naturally in the timber. In extreme cases, peeling can occur.)
- test for satisfactory adhesion by sanding and coating a small test area in advance
- on timbers that occasionally give a problem, fine-sand the surface with 180-240 grade free cut paper, then wash the floor thoroughly with WattyI Estapol 7008 Reducer. Completely mop up all residues with a soft cloth
- for recommendations outside those contained in this data sheet, refer to WattyI



SAFETY PRECAUTIONS

- flammable. Avoid contact with heat and naked flame
- avoid contact with skin and eyes
- use gloves, mask and goggles during application
- provide adequate ventilation when using in confined spaces
- this product is intended for use in industrial situations by professional applicators in accordance with the advice given on this sheet. All work involving the use and application of this product should be carried out in compliance with all relevant Health, Safety & Environmental standards and regulations and must not be used without reference to the Material Safety Data Sheet (MSDS)

PACKAGING

20 litres

For the most up to date information contact Wattyl Customer Service Hotline or visit the Wattyl Website.

	Australia	New Zealand
CUSTOMER SERVICE HOTLINE	132 101	0800 735 551
WEBSITE	http://www.wattyl.com.au	http://www.wattyl.co.nz

Wattyl and Estapol are registered trademarks of Wattyl Australia Pty Ltd.

1. This information is provided with respect to the listed Wattyl products. Wattyl recommends that: (a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product. 2. The information in this TDS was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive. 3. For all product and non-product related information, Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office. 4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.
WATTYL AUSTRALIA PTY LTD (ABN 40 000 035 914)