

# GranoRoof

Page 1 of 2  
December 2010

## DESCRIPTION

- GranoRoof is a 100% acrylic satin paint specifically formulated to withstand the harsh effects of sun and weather when applied to roofing surfaces.

## PRINCIPAL CHARACTERISTICS

- Suitable for exterior use only.
- Designed to be applied to most exterior roofing surfaces.
- Excellent durability.

## COLOURS AND GLOSS

- Bases may be tinted to achieve specific colours as required.
- Satin

## BASIC DATA

- **Surface Dry** Thirty (30) minutes.
- **Recoat** Two (2) hours.
- **Fully Cured** Seven (7) days.  
All figures are quoted at 25°C and 50% relative humidity. Drying will take longer at lower temperatures or higher relative humidity.
- **Coverage per coat:** up to 7 M<sup>2</sup>/L (depending on the surface porosity and method of application).
- **Wet Film Thickness** 140 micron
- **Dry Film Thickness** 55 micron
- **Thinning** Not required, however may be thinned sparingly with water.
- **Clean-up** Thoroughly clean equipment with water.

## RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- Suitable for use on most exterior roofing surfaces including weathered concrete tiles, zincalume, galvanised steel, Colorbond® and previously painted surfaces in good condition.
- Ensure the surface is clean and dry. All loose, peeling and flaking material must be removed prior to coating.
- Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process. Application **should not** be carried out if rain is likely to occur before the paint has dried.
- Any mould spots must be treated with bleach, and then rinsed with clean water before painting. For added protection use Watty! Fungicidal Additive in the paint; however this should not be used where roofs are used for collecting drinking water.
- Not suitable for walk on surfaces.
- Not suitable for use on terracotta or glazed ceramic tiles.
- For specific substrate preparation, see relevant specification sheets.
- On roofs used for collecting rainwater downpipes must be disconnected from tanks before painting, and not reconnected until after the roof has been thoroughly rinsed by repeated heavy rainfalls.
- On roofs where drinking water is collected a first-flush water diverter system must be installed.

## INSTRUCTIONS FOR USE

- Stir contents thoroughly with a flat stirrer before and during use.
- Apply two coats to a correctly prepared and primed surface by brush, roller or spray equipment.

## SAFETY DATA

- **Caution** Provide adequate ventilation during use.
- **Spills and Disposal** Do not allow spilled material to enter drains or other watercourses. Absorb spills with sand or other inert material. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local Council regarding the disposal of empty paint containers
- **M.S.D.S** A Material Safety Data Sheet (M.S.D.S.) is available on request.
- **First Aid**  
If swallowed **do not** induce vomiting. Give plenty of water to drink. Contact a doctor or the Poisons Information Centre. Phone 131126 (Australia).  
If in eyes, hold eyes open and flood with water for at least 15 minutes. Contact a doctor if any irritation occurs.  
If on skin remove contaminated clothing, wash skin thoroughly with soap and water or a proprietary skin cleanser. Do not use solvents.  
If affected by inhalation remove person to fresh air. If breathing difficulties persist or occur later, contact a doctor.

## ADDITIONAL DATA

- Available in 15 litre containers.
- Containers must be secured and stored upright during transit.
- Containers must not be exposed to excessive heat or cold.
- For further information, contact the Wattyl Information Hotline. Phone 132101(Australia).

1. This information is provided with respect to the listed Granosite products. Wattyl recommends that:  
(a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Wattyl; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.
2. The information in this technical data sheet was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl cannot guarantee that the information provided is wholly comprehensive.
3. Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl Office.
4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.