



# STRIPAWAY

TM12.50

## DESCRIPTION

- a non-caustic paint removing gel for timber

## PRINCIPAL CHARACTERISTICS

- easy to apply, removes old lacquer, varnish, enamel, and films of 'French polish'
- can also be used to soften and rejuvenate old paint brushes
- designed for application to vertical and horizontal surfaces

Note: We advise that you test this product to determine if it is suitable for your particular use.

## COLOUR AND GLOSS

- not applicable

## INSTRUCTIONS FOR USE

- agitate thoroughly with a flat-bladed stirrer before and during use
- apply a liberal coating with an old paint brush
- allow the surface to soften thoroughly before attempting to remove the film. Test after 10 minutes. If not completely soft, re-test at 10 minutes intervals, then remove with a paint scraper
- if left too long the surface will re-harden, requiring reapplication of Stripaway to soften
- wash down using steel-wool lubricated with water, Watty T10 or T35 Thinner and allow to dry thoroughly
- prepare the substrate as required by the finishing system
- shelf life (cool and dry place) at least 12 months in unopened containers
- for recommendations outside those contained in this data sheet, refer to Watty

## SAFETY PRECAUTIONS

- avoid contact with skin and eyes
- use gloves, mask and goggles during application
- provide adequate ventilation when using in confined spaces
- may build up pressure on storage, open with care
- this product is intended for use in industrial situations by professional applicators in accordance with the advice given on this sheet. All work involving the use and application of this product should be carried out in compliance with all relevant Health, Safety & Environmental standards and regulations and must not be used without reference to the Material Safety Data Sheet (MSDS)

## PACKAGING

20 litres

For the most up to date information contact Watty Customer Service Hotline or visit the Watty Website.

|                                 |   |   |
|---------------------------------|---|---|
|                                 | <b>Australia</b>  | <b>New Zealand</b>  |
| <b>CUSTOMER SERVICE HOTLINE</b> | 132 101   | 0800 735 551  |
| <b>WEBSITE</b>                  | <a href="http://www.wattyl.com.au">http://www.wattyl.com.au</a> | <a href="http://www.wattyl.co.nz">http://www.wattyl.co.nz</a> |

Watty is a registered trademark of Watty Australia Pty Ltd.

1. This information is provided with respect to the listed Watty products. Watty recommends that: (a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Watty; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product. 2. The information in this TDS was prepared using information gathered during product development. While Watty endeavours to update this information and maintain the accuracy and currency of its contents, Watty cannot guarantee that the information provided is wholly comprehensive. 3. For all product and non-product related information, Watty recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Watty Office. 4. To the full extent permitted by law, Watty's liability for breach of a condition or warranty implied into the contract for sale between Watty and you by law is limited at Watty's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.  
WATTYL AUSTRALIA PTY LTD (ABN 40 000 035 914)