



**DESCRIPTION**

- a quick-drying water-based timber putty for interior and exterior use

**PRINCIPAL CHARACTERISTICS**

- fast drying
- for filling nail-holes and minor imperfections in timbers used for wall-panelling and other interior woodwork
- suitable for internal use under clear finishes, stains, lacquer, varnish and French polish
- suitable for exterior use under pigmented coatings

Note: We advise that you test this product to determine if it is suitable for your particular use.

**COLOUR AND GLOSS**

- available in a range of timber tones, cypress, oak, pine, cedar, contemporary maple, rosewood, teak walnut and jarrah

**BASIC DATA AT 25° C and 50% RELATIVE HUMIDITY**

- touch-dry ..... 10 minutes
- sandable ..... 30 minutes
- shelf life (cool, dry place) ..... at least 12 months in unopened container

**SURFACE PREPARATION**

- all surfaces must be free from wax, silicone, oil and other contaminants
- may be applied to bare timber, (a neater job is obtained when a sealer is applied first)
- sand smooth with 180-240 grade fre-cut paper, and remove all sanding dust
- if required, stain the surface using WattyI Craftsman® Dye Stain Fast, Slow or Craftsman Pigmented Stain, wipe off excess stain

**INSTRUCTIONS FOR USE**

- thinning not required however, if product has thickened, it may be thinned sparingly with water
- press putty lightly into position, leaving a little standing slightly above the surface
- for deeper holes, a second application should be made after the first coat has hardened sufficiently
- allow to dry for approximately 30 minutes, then sand smooth with 180-240 grade fre-cut paper
- remove all traces of sanding-dust prior to application of other coatings
- seal and topcoat with a suitable WattyI system
- clean up with water
- for recommendations outside those contained in this data sheet, refer to WattyI



**SAFETY PRECAUTIONS**

- flammable. Avoid contact with heat and naked flame
- avoid contact with skin and eyes
- use gloves, mask and goggles during application
- provide adequate ventilation when using in confined spaces
- this product is intended for use in industrial situations by professional applicators in accordance with the advice given on this sheet. All work involving the use and application of this product should be carried out in compliance with all relevant Health, Safety & Environmental standards and regulations and must not be used without reference to the Material Safety Data Sheet (MSDS)

**PACKAGING**

75 grams

For the most up to date information contact WattyL Customer Service Hotline or visit the WattyL Website.

	<b>Australia</b>	<b>New Zealand</b>
<b>CUSTOMER SERVICE HOTLINE</b>	<b>132 101</b>	<b>0800 735 551</b>
<b>WEBSITE</b>	<a href="http://www.wattyl.com.au">http://www.wattyl.com.au</a>	<a href="http://www.wattyl.co.nz">http://www.wattyl.co.nz</a>

WattyL and Craftsman are registered trademarks of WattyL Australia Pty Ltd.

1. This information is provided with respect to the listed WattyL products. WattyL recommends that: (a) you review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by WattyL; (c) the product be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product. 2. The information in this TDS was prepared using information gathered during product development. While WattyL endeavours to update this information and maintain the accuracy and currency of its contents, WattyL cannot guarantee that the information provided is wholly comprehensive. 3. For all product and non-product related information, WattyL recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest WattyL Office. 4. To the full extent permitted by law, WattyL's liability for breach of a condition or warranty implied into the contract for sale between WattyL and you by law is limited at WattyL's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.  
WATTYL AUSTRALIA PTY LTD (ABN 40 000 035 914)