

|                    |                             |
|--------------------|-----------------------------|
| System:            | GranoRoll-on Medium Impact  |
| Interior/Exterior: | Exterior                    |
| Substrate:         | Brickwork/Blockwork/Masonry |

Version 8

25/08/2021

## Product Description

GranoRoll-on Medium® is an acrylic, high performance coating containing sand which is applied by black texture roller or 18mm pile roller to achieve a medium profile sandy texture.

## Surface Preparation

Substrate must be free from dirt, dust, oil, grease, mould or any other contaminants that may affect adhesion. All scaling, efflorescence, mould, mastic compound or any other foreign material must be removed prior to painting. Remove all traces of loosely adhering material by scraping, grinding or wire brushing, etc.

Render surface with the appropriate GranoRender®. Allow to cure 7 days. There must be less than 15% moisture content in the surface at the time of application.

For raked joints apply in two coats first filling the joints flush with brickwork then skim coating the whole surface. For flush joints apply one coat directly to the surface.

## Coatings System

|                         | First Coat:            | Second Coat:         | Third Coat:                              | Fourth Coat:                      |
|-------------------------|------------------------|----------------------|------------------------------------------|-----------------------------------|
|                         | GranoRender®           | GranoPrime®          | GranoRoll-on Medium™                     | GranoImpact®                      |
| Technical Data Sheet No | G1.17, G1.18, G1.25    | G1.02                | G2.21                                    | G2.01                             |
| A.P.A.S. Specification  | -                      | -                    | -                                        | APAS 0117/3                       |
| Australian Standard     | -                      | -                    | -                                        | AS4548.3                          |
| Application Method      | Stainless steel trowel | Brush, roller, spray | Black texture roller or 18mm pile roller | Brush, 10-12mm pile roller, spray |
| Clean-Up/Thinners       | Water                  | Water                | Water                                    | Water                             |
| Spreading Rate          | 4 Kg/m2                | 12.5 m2/L            | 1.6 m2/L                                 | 5 m2/L                            |
| Dry Film Thickness      | 2000-8000 microns      | 20 microns           | 380 microns                              | 95 microns                        |
| Recoat                  | 7 days                 | 6 hours              | 24 hours                                 | 6 hours                           |

## Additional Notes

Surface preparation is the responsibility of the Builder, Renovator or Main Contractor and the Applicator. To achieve the indicated performance, it must be carried out according to Wattyl's recommendations. Application is to be carried out by a skilled applicator, who is totally conversant with the Wattyl Granosite products and systems, to validate full material warranty conditions.

Caution: Provide adequate ventilation during use. Application should not be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

---

**REFER TO PRODUCT TECHNICAL DATA SHEETS AND SAFETY DATA SHEETS FOR FURTHER INFORMATION ON THE PRODUCTS MENTIONED IN THIS SPECIFICATION SHEET**

1 This information is provided with respect to the listed products. Please (a) Review the Technical Data Sheet (TDS) and Safety Data Sheet (SDS) before you use or handle the product; (b) Transport, handle and use the product in accordance with the relevant TDS, SDS and instructions; and (c) Thoroughly test the product on a sample of intended substrate, before using the product.

2 While we try to maintain the accuracy of this information, we cannot guarantee that the information is wholly comprehensive. Please conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely before using the product, or contact us if you require further information.

3 If you are not a Consumer as defined by Australian Consumer Law or New Zealand Consumer Law (from hereon referred to as "the law"), we are not liable for breach of any warranty, term, condition, guarantee or similar, or any loss or damage including any special, incidental or consequential damages suffered by you, to the full extent permitted by law. Our liability is limited, at our option, to the replacement of nonconforming product or a refund of the product purchase price. These limitations do not apply to you if the product was acquired by you as a Consumer under the law. A person who buys a good in trade or commerce for the purpose of re-supply; to use them up or transform the goods in the course of a process of production or manufacture; or in the course of repairing or treating other goods or fixtures on land, has not acquired the good as a consumer under the law. If you are a Consumer as defined by the law, and you are buying goods which are not ordinarily acquired for personal, domestic or household use or consumption, our liability for breach of any warranty, term, condition, guarantee or similar, is limited to the full extent permitted by law, at our option, to the replacement of the product or a refund of the product purchase price.

All brands and product names are registered trademarks of Hempel (Wattyl) Australia Pty Ltd ABN 40 000 035 914 and Hempel (Wattyl) New Zealand Ltd 942 904 073 3692.

[www.wattyl.com.au](http://www.wattyl.com.au)

[www.wattyl.co.nz](http://www.wattyl.co.nz)

WATTYL ASSIST: Ph: 132 101 (AUSTRALIA)

Ph: 0800 825 7727 (NEW ZEALAND)

# SAFETY DATA SHEET

GRANORENDER PM MEDIUM

851014

## Section 1. Identification

**Product identifier** : GRANORENDER PM MEDIUM

**Product code** : 851014

**Product type** : Solid.

### Relevant identified uses of the substance or mixture and uses advised against

**Material uses** : Paint or paint related material.

**Supplier's details** : VALSPAR PAINT (AUSTRALIA) PTY LTD  
L3, 2 Burbank Place,  
Norwest, NSW, 2153  
wattyl@wattyl.com.au

**Emergency telephone number (with hours of operation)** : +(61)290372994 (Available 24 hrs/ 7 days)

## Section 2. Hazard(s) identification

**Classification of the substance or mixture** : SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1  
SKIN SENSITISATION - Category 1  
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

### GHS label elements

**Hazard pictograms** :



**Signal word** : DANGER

**Hazard statements** : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
May cause respiratory irritation.  
Causes damage to organs through prolonged or repeated exposure.

### Precautionary statements

**General** : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**Prevention** : Wear protective gloves. Wear eye or face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

**Response** : Get medical advice/attention if you feel unwell. IF INHALED: Call a POISON CENTER or doctor if you feel unwell. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

## Section 2. Hazard(s) identification

- Storage** : Store locked up. Store in a well-ventilated place. Keep container tightly closed.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
- Other hazards which do not result in classification** : None known.

## Section 3. Composition and ingredient information

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

### CAS number/other identifiers

Not available.

| Ingredient name                       | % (w/w)  | CAS number |
|---------------------------------------|----------|------------|
| crystalline silica, respirable powder | >60%     | 14808-60-7 |
| Portland Cement                       | 30 - 60% | 65997-15-1 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

## Section 4. First aid measures

waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Firefighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : No specific fire or explosion hazard.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
metal oxide/oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 5. Firefighting measures

**Hazchem code** : Not applicable.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

- Small spill** : Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. Avoid release to the environment.

## Section 8. Exposure controls and personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name                       | Exposure limits                                                                                                   |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| crystalline silica, respirable powder | <b>Safe Work Australia (Australia, 12/2019).</b><br>TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form:<br>Respirable dust |
| Portland Cement                       | <b>Safe Work Australia (Australia, 12/2019).</b><br>TWA: 10 mg/m <sup>3</sup> 8 hours.                            |

### Biological limit values

: There is no biological limit allocated.

### Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

### Skin protection

#### Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

|                                              |                                                                   |
|----------------------------------------------|-------------------------------------------------------------------|
| Physical state                               | : Solid.                                                          |
| Colour                                       | : Off-white.                                                      |
| Odour                                        | : Not available.                                                  |
| Odour threshold                              | : Not available.                                                  |
| pH                                           | : Not applicable.                                                 |
| Melting point                                | : Not available.                                                  |
| Boiling point                                | : Not available.                                                  |
| Flash point                                  | : Closed cup: Not applicable.                                     |
| Evaporation rate                             | : Not available.                                                  |
| Flammability (solid, gas)                    | : Not available.                                                  |
| Lower and upper explosive (flammable) limits | : Not available.                                                  |
| Vapour pressure                              | : Not relevant/applicable due to nature of the product.           |
| Vapour density                               | : Not available.                                                  |
| Relative density                             | : 2.82                                                            |
| Solubility                                   | : Not available.                                                  |
| Partition coefficient: n-octanol/water       | : Not available.                                                  |
| Auto-ignition temperature                    | : Not available.                                                  |
| Decomposition temperature                    | : Not available.                                                  |
| Viscosity                                    | : Kinematic (40°C (104°F)): >0.205 cm <sup>2</sup> /s (>20.5 cSt) |

### Aerosol product

|                    |          |
|--------------------|----------|
| Heat of combustion | : 0 kJ/g |
|--------------------|----------|

## Section 10. Stability and reactivity

|                                    |                                                                                                        |
|------------------------------------|--------------------------------------------------------------------------------------------------------|
| Reactivity                         | : No specific test data related to reactivity available for this product or its ingredients.           |
| Chemical stability                 | : The product is stable.                                                                               |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| Conditions to avoid                | : No specific data.                                                                                    |
| Incompatible materials             | : No specific data.                                                                                    |
| Hazardous decomposition products   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Not available.

#### Irritation/Corrosion

Not available.

#### Sensitisation

## Section 11. Toxicological information

Not available.

### Mutagenicity

Not available.

### Carcinogenicity

Not available.

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

| Name            | Category   | Route of exposure | Target organs                |
|-----------------|------------|-------------------|------------------------------|
| Portland Cement | Category 3 | -                 | Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

| Name                                  | Category   | Route of exposure | Target organs |
|---------------------------------------|------------|-------------------|---------------|
| crystalline silica, respirable powder | Category 1 | inhalation        | -             |

### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

## Section 11. Toxicological information

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

**General** : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Not available.

## Section 12. Ecological information

### Toxicity

Not available.

### Persistence and degradability

Not available.

### Bioaccumulative potential

Not available.

### Mobility in soil

**Soil/water partition coefficient ( $K_{oc}$ )** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and

## Section 13. Disposal considerations

its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                            | ADG                                    | ADR/RID         | IMDG            | IATA            |
|----------------------------|----------------------------------------|-----------------|-----------------|-----------------|
| UN number                  | Not regulated.                         | Not regulated.  | Not regulated.  | Not regulated.  |
| UN proper shipping name    | Not regulated.                         | Not regulated.  | Not regulated.  | Not regulated.  |
| Transport hazard class(es) | Not regulated.                         | Not regulated.  | Not regulated.  | Not regulated.  |
| Packing group              | Not applicable.                        | Not applicable. | Not applicable. | Not applicable. |
| Environmental hazards      | Not applicable.                        | Not applicable. | Not applicable. | Not applicable. |
| Additional information     | <u>Hazchem code</u><br>Not applicable. | Not applicable. | Not applicable. | Not applicable. |

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

## Section 15. Regulatory information

### Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

### Model Work Health and Safety Regulations - Scheduled Substances

| <u>Ingredient name</u>                | <u>Schedule</u>                                                          |
|---------------------------------------|--------------------------------------------------------------------------|
| crystalline silica, respirable powder | Prohibited [For abrasive blasting at a concentration of greater than 1%] |

### Agricultural and Veterinary Chemicals Code Act 1994

Not available.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

## Section 15. Regulatory information

Not listed.

## Section 16. Any other relevant information

### History

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Date of printing</b>               | : 22, April, 2021.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Date of issue/Date of revision</b> | : 22, April, 2021                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Date of previous issue</b>         | : 22, April, 2021                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Version</b>                        | : 1.04                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Key to abbreviations</b>           | : ADG = Australian Dangerous Goods<br>ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road<br>ATE = Acute Toxicity Estimate<br>BCF = Bioconcentration Factor<br>GHS = Globally Harmonized System of Classification and Labelling of Chemicals<br>IATA = International Air Transport Association<br>IBC = Intermediate Bulk Container<br>IMDG = International Maritime Dangerous Goods<br>LogPow = logarithm of the octanol/water partition coefficient<br>MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)<br>N/A = Not available<br>SUSMP = Standard Uniform Schedule of Medicine and Poisons<br>UN = United Nations |

### Procedure used to derive the classification

| Classification                                                                               | Justification      |
|----------------------------------------------------------------------------------------------|--------------------|
| SKIN CORROSION/IRRITATION - Category 2                                                       | Calculation method |
| SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                                               | Calculation method |
| SKIN SENSITISATION - Category 1                                                              | Calculation method |
| SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3 | Calculation method |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1                              | Calculation method |

**References** : Not available.

Indicates information that has changed from previously issued version.

### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become make themselves aware of and understand the data contained in this SDS and any hazards that may be associated with the product. This information is provided in good faith and believed to be accurate as of the effective date mentioned herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can may change later the composition, hazards and risks of the product. Products shall should not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to, the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for the use of the product are not under the manufacturer's control of the manufacturer; the customer/buyer/user is responsible to for determine determining the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS, without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be held responsible for SDSs obtained from any other source.

## End of SDS



TEXTURE SOLUTIONS  
GRANORENDER PM MEDIUM

RESOURCE CODE 851014

SEPTEMBER 2021

PAGE 1 OF 3



## Description &amp; Uses

GranoRender PM Medium is a high quality pre-blended, polymer modified cementitious rendering and screeding material with excellent spray and trowel application properties. GranoRender PM Medium has been specifically designed for thin section rendering in one application of 2-6mm. Applications less than 2mm require the addition of GranoBond to the gauging water. GranoRender PM Medium applies with exceptional ease to provide a wood float or sponge finish. GranoRender PM Medium has superior application and adhesion properties when compared to conventional sand and cement render.

## Features &amp; Benefits

- Applied up to 2-6mm in a single application.
- Applies with ease to provide a wood float or sponge finish
- Excellent spray application properties
- Superior application and adhesion properties when compared to conventional sand and cement render

## Colours &amp; Gloss

Grey.

Matt.

## Properties &amp; Performance Guide

|                     |                                                                                                                            |
|---------------------|----------------------------------------------------------------------------------------------------------------------------|
| Dry & Recoat Times  | Surface Dry - 4 hours                                                                                                      |
|                     | Recoat - 24 hours (when recoating with itself, if required)                                                                |
|                     | Fully Cured - 7 days                                                                                                       |
|                     | Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity. |
| Consistency         | Dry powder.                                                                                                                |
| Texture             | Grainy.                                                                                                                    |
| Pot Life            | 3-4 hours when mixed.                                                                                                      |
| Coverage            | 4.00 Kg/M <sup>2</sup> (per 2mm film thickness).                                                                           |
| Clean Up            | Thoroughly clean equipment with water away from drains.                                                                    |
| Weatherability      | Excellent.                                                                                                                 |
| Abrasion Resistance | Excellent.                                                                                                                 |

TEXTURE SOLUTIONS  
GRANORENDER PM MEDIUM

RESOURCE CODE 851014

SEPTEMBER 2021

PAGE 2 OF 3

## Recommended Substrate Conditions &amp; Preparation

Surfaces are to be suitably prepared in accordance with proper trade practices.

GranoRender PM Medium is suitable for application to autoclaved aerated concrete (AAC) blocks or panels, off-form concrete and any other fair-faced, flush and straight laid concrete block or brickwork (common, clay, Calsil®, and extruded bricks), conpolcrete, and some types of extruded & expanded polystyrene blocks and panels.

Surface preparation is the responsibility of the Builder, Renovator or Main Contractor and the Applicator. To achieve the indicated performance, application must be carried out according to Watty's recommendations.

Ensure the surface is clean and dry. All substrates must be free of dirt, dust, grease, oil, mould release agents, bondbreakers and any other contaminants that may interfere with adhesion.

Fresh cementitious substrates should be left for 14-28 days before coating. There must be less than 15% moisture content in the surface at the time of coating to ensure optimum coating performance.

**Note:** Porous substrates **must** be sealed with GranoBond Sealcoat (G1.01). Apply by roller or spray at 0.2 L/M<sup>2</sup> (5M<sup>2</sup>/L) and allow to dry 2-6 hours **prior** to applying GranoRender PM Medium.

For specific substrate preparation, see relevant specification sheets.

## Application Guide

**Application greater than 2mm thickness.**

Mix one (1) 20Kg bag of GranoRender PM Medium to approximately 4L of water. Add the powder to the water steadily and mix with a power stirrer until it is smooth and lump free. GranoRender PM Medium has a pot life of 3-4 hours when mixed.

Trowel one (1) coat of GranoRender PM Medium @ 8.00 Kg/M<sup>2</sup> per 4mm film thickness. Allow 24 hours to dry. Apply an additional coat of GranoRender PM Medium if required.

**Application less than 2mm thickness.**

For applications less than 2mm of GranoRender PM Medium, dilute GranoBond (G1.01) 1 part to 4 parts water and use this "milk" in place of gauging water.

Mix one (1) 20kg bag of GranoRender PM Medium to approximately 4L of GranoBond Milk. Add the powder to the GranoBond Milk steadily and mix with a power stirrer until it is smooth and lump free. GranoRender PM Medium has a pot life of 3-4 hours when mixed.

Trowel one (1) coat of GranoRender PM Medium @ 4.00 Kg/M<sup>2</sup> per 2mm film thickness. Allow 24 hours to dry. Apply an additional coat of GranoRender PM Medium if required.

**Curing.**

Keep damp for the first 12 hours to ensure full curing strength is developed. This is critical in windy conditions or when humidity is low.

Allow to cure for 7 days or until there is less than 15% moisture content before topcoating.

Cementitious render products should be allowed to stand for 5 minutes after initial mixing to allow proper activation of the cement, and then be re-mixed before use.

Freshly applied material must be protected from frosts and rain for a minimum of 48 hours.

Application should not be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C or when humidity is very high. The temperature must not fall below 10°C during the drying process.

In exterior application avoid painting when dew or rain is likely.

TEXTURE SOLUTIONS  
GRANORENDER PM MEDIUM

RESOURCE CODE 851014

SEPTEMBER 2021

PAGE 3 OF 3

## Additional Data

Available in 20Kg bag.

**SHELF LIFE:** Six (6) months, if stored appropriately. This must include storage under cover, above ground, away from direct heat and moisture.

Not suitable for walk-on surfaces.

GranoRender PM Medium is a surface preparation product and is used in conjunction with various Wattyl Granosite systems. As such, it is not a system in itself and should only be used where specified.

**Note:** The approved Wattyl Granosite system should be applied to GranoRender PM Medium within 3 months of curing. Leave 7 days after application of final coat before washing. Wash using a sponge or soft cloth with warm water and mild detergent. Avoid harsh scrubbing and strong household cleaners.

Bags must be dry during transport and storage.

Bags must not be exposed to moisture, excessive heat or cold.

It is recommended that application be carried out by a skilled applicator, who is totally conversant with the Granosite products and systems, to validate full material warranty conditions.

The use of proprietary additives other than those manufactured by Wattyl is not recommended.

Do not use for any other purpose other than as specified in our literature.

## Safety Data

## First Aid Instructions

For advice, contact the Poisons Information Centre on 131 126 (Australia), 0800 764 766 (New Zealand), or a doctor.  
If swallowed, do not induce vomiting. Give a glass of water to drink.  
If in eyes, wash out immediately with water.  
If inhaled remove from contaminated area to fresh air.  
If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.

## Safety Directions

Keep out of reach of children.  
Avoid contact with skin and eyes.  
Ensure adequate ventilation during use.  
Avoid prolonged breathing of vapour.  
Wash hands thoroughly after use.

## Further Information

For the latest information refer to the Safety Data Sheet available on our websites.  
Australia: [www.wattyl.com.au](http://www.wattyl.com.au) or contact Wattyl Assist on 132 101.  
New Zealand: [www.wattyl.co.nz](http://www.wattyl.co.nz) or contact Wattyl Assist on 0800 825 7727.

1. This information is provided with respect to the listed Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand products. Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand, hereon referred to as "Hempel (Wattyl)," recommends that:

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Hempel (Wattyl); (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in the TDS was prepared using information gathered during product development. While Hempel (Wattyl) endeavour to update this information and maintain the accuracy of its contents, Hempel (Wattyl) cannot guarantee that the information is wholly comprehensive.

3. Hempel (Wattyl) recommend that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest office of Hempel (Wattyl).

4. To the full extent permitted by law, the liability of Hempel (Wattyl) for breach of a condition or warranty implied into the contract for sale between Hempel (Wattyl) and you by law is limited at the election of Hempel (Wattyl) to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

All brands and product names are registered trademarks of Hempel (Wattyl) Australia Pty Ltd ABN 40 000 035 914 and Hempel (Wattyl) New Zealand Pty Ltd 942 904 073 3692.

Calsil® is a registered trademark of Boral Resources (Vic) Pty Ltd.

WATTYL ASSIST: Ph: 132 101 (AUSTRALIA)  
Ph: 0800 825 7727 (NEW ZEALAND)

Conforms to Model Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals - Australia

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : WATTYL GRANOSITE GRANOPRIME  
Product identity : 852001  
Product type : Paint or paint related material

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : buildings  
Identified uses : Consumer applications, Professional applications, Used by spraying.

#### 1.3 Details of the supplier of the safety data sheet

Company details : Hempel (Wattyl) Australia Pty Ltd.  
Level 3, 2 Burbank Place  
Norwest, , New South Wales 2153  
Australia  
Tel: +(61) 288673333  
Email: wattyl@wattyl.com.au  
Date of Preparation : 2 May 2024  
Date of previous issue : No previous validation.

#### 1.4 Emergency telephone number

Emergency telephone number (with hours of operation)  
  
Poisons Information Centre.  
Tel.: 13 11 26 (24 hour)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### GHS Classification

Not classified.

#### 2.2 Label elements

Hazard pictograms :  
Signal word : No signal word.  
Hazard statements : No known significant effects or critical hazards.  
Precautionary statements :  
General : Keep out of reach of children. If medical advice is needed, have product container or label at hand.  
Supplemental label elements : Not applicable.

#### 2.3 Other hazards

Other hazards which do not result in classification : None known.

### SECTION 3: Composition/information on ingredients

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.  
If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).  
Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. In all cases of doubt, or when symptoms persist, seek medical attention.  
Inhalation : Remove to fresh air.  
Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

### SECTION 4: First aid measures

|                              |                                                                                                                                                                                                                                                          |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ingestion :                  | If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat. |
| Protection of first-aiders : | No action shall be taken involving any personal risk or without suitable training.                                                                                                                                                                       |

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

|                |                                                   |
|----------------|---------------------------------------------------|
| Eye contact :  | No known significant effects or critical hazards. |
| Inhalation :   | No known significant effects or critical hazards. |
| Skin contact : | No known significant effects or critical hazards. |
| Ingestion :    | No known significant effects or critical hazards. |

##### Over-exposure signs/symptoms

|                |                   |
|----------------|-------------------|
| Eye contact :  | No specific data. |
| Inhalation :   | No specific data. |
| Skin contact : | No specific data. |
| Ingestion :    | No specific data. |

#### 4.3 Indication of any immediate medical attention and special treatment needed

|                       |                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| Notes to physician :  | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments : | No specific treatment.                                                                                                    |

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

|                       |                                                                                                            |
|-----------------------|------------------------------------------------------------------------------------------------------------|
| Extinguishing media : | Recommended: alcohol resistant foam, CO <sub>2</sub> , powders, water spray.<br>Not to be used : waterjet. |
|-----------------------|------------------------------------------------------------------------------------------------------------|

#### 5.2 Special hazards arising from the substance or mixture

|                                         |                                                                                              |
|-----------------------------------------|----------------------------------------------------------------------------------------------|
| Hazards from the substance or mixture : | In a fire or if heated, a pressure increase will occur and the container may burst.          |
| Hazardous combustion products :         | Decomposition products may include the following materials: carbon oxides metal oxide/oxides |

#### 5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Hazchem code : -

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training.

#### 6.2 Environmental precautions

Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13).

#### 6.4 Reference to other sections

### SECTION 6: Accidental release measures

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### 7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

| Product/ingredient name        | Exposure limit values |
|--------------------------------|-----------------------|
| No exposure limit value known. |                       |

#### Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### 8.2 Exposure controls

##### Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

##### Individual protection measures

General :

Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.



Hygiene measures :

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.

Eye/face protection :

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Hand protection :

Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.

Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:

Recommended: Silver Shield / Barrier / 4H gloves, nitrile rubber (>0.3 mm), neoprene rubber (>0.1 mm), butyl rubber (>0.5 mm), natural rubber (latex) (>0.4 mm), polyvinyl chloride (PVC), Viton®, nitrile rubber (>0.1 mm), butyl rubber (>0.3 mm)  
Short term exposure: polyvinyl alcohol (PVA)

Body protection :

Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.

Respiratory protection :

### SECTION 8: Exposure controls/personal protection

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

|                                                |                                                                     |
|------------------------------------------------|---------------------------------------------------------------------|
| Physical state :                               | Liquid.                                                             |
| Odour :                                        | Non-characteristic.                                                 |
| pH :                                           | Testing not relevant or not possible due to nature of the product.  |
| Melting point/freezing point :                 | 0°C This is based on data for the following ingredient: water       |
| Boiling point/boiling range :                  | Testing not relevant or not possible due to nature of the product.  |
| Flash point :                                  | Closed cup: 101°C (213.8°F)                                         |
| Evaporation rate :                             | Testing not relevant or not possible due to nature of the product.  |
| Flammability :                                 | Not available.                                                      |
| Lower and upper explosive (flammable) limits : | No specific data.                                                   |
| Vapour pressure :                              | 2.333 kPa This is based on data for the following ingredient: water |
| Vapour density :                               | Testing not relevant or not possible due to nature of the product.  |
| Relative density :                             | 1.3 g/cm <sup>3</sup>                                               |
| Partition coefficient (LogKow) :               | Testing not relevant or not possible due to nature of the product.  |
| Auto-ignition temperature :                    | Testing not relevant or not possible due to nature of the product.  |
| Decomposition temperature :                    | Testing not relevant or not possible due to nature of the product.  |
| Viscosity :                                    | Testing not relevant or not possible due to nature of the product.  |
| Explosive properties :                         | Testing not relevant or not possible due to nature of the product.  |
| Oxidising properties :                         | Testing not relevant or not possible due to nature of the product.  |

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

The product is stable.

#### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4 Conditions to avoid

No specific data.

#### 10.5 Incompatible materials

Reactive or incompatible with the following materials: acids.

#### 10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides metal oxide/oxides

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

No known significant effects or critical hazards.

##### Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|--------|---------|------|----------|
| Not available.          |        |         |      |          |

##### Acute toxicity estimates

| Route                                             | ATE value |
|---------------------------------------------------|-----------|
| No known significant effects or critical hazards. |           |

##### Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|----------|-------------------|---------------|
| Not available.          |          |                   |               |

##### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|----------|-------------------|---------------|
| Not available.          |          |                   |               |

##### Aspiration hazard

| Product/ingredient name | Result |
|-------------------------|--------|
| Not available.          |        |

##### Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

##### Potential chronic health effects

Other information : No additional known significant effects or critical hazards.

### SECTION 12: Ecological information

#### 12.1 Toxicity

Do not allow to enter drains or watercourses.

#### 12.2 Persistence and degradability

#### 12.3 Bioaccumulative potential

#### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : No known data available in our database.

Mobility : No known data available in our database.

##### Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

The generation of waste should be avoided or minimised wherever possible. Residues of the product is not listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

##### Packaging

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

### SECTION 14: Transport information

Transport may take place according to national regulation NZS for transport by road and train, IMDG for transport by sea, IATA for transport by air.

|                   | 14.1<br>UN no. | 14.2<br>Proper shipping name | 14.3<br>Transport hazard class(es) | 14.4<br>PG* | 14.5<br>Env.* | Additional information |
|-------------------|----------------|------------------------------|------------------------------------|-------------|---------------|------------------------|
| <b>ADG Class</b>  | Not regulated. |                              | -                                  | -           | No.           | -                      |
| <b>IMDG Class</b> | Not regulated. |                              | -                                  | -           | No.           | -                      |
| <b>IATA Class</b> | Not regulated. |                              | -                                  | -           | No.           | -                      |

PG\* : Packing group

Env.\* : Environmental hazards

#### 14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Transport in bulk according to IMO instruments

Not applicable.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

| Ingredient name     | Schedule |
|---------------------|----------|
| No listed substance |          |

### SECTION 16: Other information

 Indicates information that has changed from previously issued version.

| Classification  | Justification |
|-----------------|---------------|
| Not classified. |               |

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

TEXTURE SOLUTIONS  
GRANOPRIME

RESOURCE CODE 852001

APRIL 2024

PAGE 1 OF 3



## Description &amp; Uses

GranoPrime is an acrylic primer sealer. GranoPrime can be applied by brush, roller or spray, prior to the application of most of the Wattyl Granosite texture systems. GranoPrime ensures the optimum performance of the complete coating system by stabilising irregularities in substrate adsorption and mechanical strength. On concrete, cement render and mortar joints, the use of GranoPrime minimises the threat of loss of adhesion or other problems that may arise due to the presence of residual alkali salts.

## Features &amp; Benefits

- Stabilises irregularities in substrate absorption and mechanical strength
- Speeds the application, controls the drying and ensures strong adhesion of topcoats to the substrate
- Minimises the threat of loss of adhesion or other problems that may arise due to presence of residual alkali salts
- As an acrylic, not subject to the degradation that can occur with polyvinyl acetates (PVAs) in an alkaline environment

## Colours

Off-White.

Do not tint GranoPrime.

## Properties &amp; Performance Guide

|                    |                                                                                                                            |
|--------------------|----------------------------------------------------------------------------------------------------------------------------|
| Dry & Recoat Times | Surface Dry - 2 hours                                                                                                      |
|                    | Recoat - 2-6 hours                                                                                                         |
|                    | Topcoat - Within 14 days of application                                                                                    |
|                    | Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity. |
| Density            | 1.3 Kg/L.                                                                                                                  |
| Consistency        | Milky liquid.                                                                                                              |
| Coverage           | 0.08 L/M <sup>2</sup> (12.5M <sup>2</sup> /L).                                                                             |
| Wet Film Thickness | 80 microns (approx).                                                                                                       |
| Dry Film Thickness | 20 microns (approx).                                                                                                       |

TEXTURE SOLUTIONS  
GRANOPRIME

RESOURCE CODE 852001

APRIL 2024

PAGE 2 OF 3

## Environmental Data &amp; Certifications



White Verified to Eco Choice Aotearoa (ECA) Specification EC-07-18.  
Licence No:0709054

## Properties &amp; Performance Guide...Continued

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                 |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Thinning                         | High Absorption Substrates<br>Medium Absorption Substrates<br>Low Absorption Substrates                                                                                                                                                                                                                                                                                                                                                  | Mix 1 part GranoPrime with 1 part water<br>Mix 2 parts GranoPrime with 1 part water<br>Use GranoPrime undiluted |
| Clean Up                         | Clean up with cold water away from drains.<br><b>Protect Our Environment:</b> Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first. |                                                                                                                 |
| VOC (Volatile Organic Compounds) | VOC < 10g/L.                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                 |

## Recommended Substrate Conditions &amp; Preparation

Surfaces are to be suitably prepared in accordance with proper trade practices.

**High Absorption Substrates:** Concrete block, Calsil® brick, autoclaved aerated concrete (AAC).

**Medium Absorption Substrates:** Off-form concrete under 40 MPa, cement render, ExoTec®, CFC, fibre cement sheeting, coloured renders, lime washes, GranoRender Coarse (G1.18), GranoRender PM Medium (G1.25), GranoRender Sponge Fine Finish (G1.17), GranoReady Render (G1.12), GranoSponge Fine Acrylic (G1.21), GranoPatch Smooth (G1.04), GranoPatch Spackle (G1.05), GranoFlex (G1.15).

**Low Absorption Substrates:** Previously painted surfaces, off-form concrete over 40 MPa, high density bricks.

GranoPrime is **not suitable** for application to steel or timber surfaces.

GranoPrime may be used as part of the GranoRoof system for properly cleaned concrete roof tiles.

Surface preparation is the responsibility of the Builder, Renovator or Main Contractor and the Applicator. To achieve the indicated performance, application must be carried out according to Wattyl's recommendations.

Ensure the surface is clean and dry. All substrates must be free of dirt, dust, grease, oil, mould release agents, bond-breakers and any other contaminants that may interfere with adhesion.

Fresh cementitious substrates should be left for 14-28 days before coating. There must be less than 15% moisture content in the surface at the time of coating to ensure optimum coating performance.

For specific substrate preparation, see relevant specification sheets.

## Application Guide

Stir contents thoroughly with a power stirrer before use.

Apply one coat to a correctly prepared surface by brush, roller or spray.

**AIRLESS GUN SETTINGS:** Tip 519 or 521. Pressure Setting 1500-2000psi.

Freshly applied material must be protected from frosts and rain for a minimum of forty-eight (48) hours.

Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C or when humidity is very high. The temperature must not fall below 10°C during the drying process.

In exterior application avoid painting when dew or rain is likely.

TEXTURE SOLUTIONS  
GRANOPRIME

RESOURCE CODE 852001

APRIL 2024

PAGE 3 OF 3

## Additional Data

Available in 15 litre containers.

Not suitable for walk-on surfaces.

GranoPrime is a surface preparation product and is used in conjunction with various Wattyl Granosite systems. As such, it is not a system in itself and should only be used where specified.

**Note:** The approved Wattyl Granosite system should be applied to GranoPrime within 14 days of curing and the GranoPrime should be protected from rain and frost for this period.

Leave 7 days after application of final coat before washing. Wash using a sponge or soft cloth with warm water and mild detergent. Avoid harsh scrubbing and strong household cleaners.

Containers must be secured and stored upright during transit.

Containers must not be exposed to excessive heat or cold.

Storage must be under cover, away from direct heat, freezing and moisture, in well-sealed containers.

It is recommended that application be carried out by a skilled applicator, who is totally conversant with the Granosite products and systems, to validate full material warranty conditions.

The use of proprietary additives other than those manufactured by Wattyl is not recommended.

Do not use for any other purpose other than as specified in our literature.

## Safety Data

## First Aid Instructions

For advice, contact the Poisons Information Centre on 131 126 (Australia), 0800 764 766 (New Zealand), or a doctor.

If swallowed, do not induce vomiting. Give a glass of water to drink.

If in eyes, wash out immediately with water.

If inhaled remove from contaminated area to fresh air.

If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.

## Safety Directions

Keep out of reach of children.

Avoid contact with skin and eyes.

Ensure adequate ventilation during use.

Avoid prolonged breathing of vapour.

Wash hands thoroughly after use.

## Further Information

For the latest information refer to the Safety Data Sheet available on our websites.

Australia: [www.wattyl.com.au](http://www.wattyl.com.au) or contact Wattyl Assist on 132 101.

New Zealand: [www.wattyl.co.nz](http://www.wattyl.co.nz) or contact Wattyl Assist on 0800 825 7727.

1. This information is provided with respect to the listed Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand products. Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand, hereon referred to as "Hempel (Wattyl)," recommends that:

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Hempel (Wattyl); (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in the TDS was prepared using information gathered during product development. While Hempel (Wattyl) endeavour to update this information and maintain the accuracy of its contents, Hempel (Wattyl) cannot guarantee that the information is wholly comprehensive.

3. Hempel (Wattyl) recommend that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest office of Hempel (Wattyl).

4. To the full extent permitted by law, the liability of Hempel (Wattyl) for breach of a condition or warranty implied into the contract for sale between Hempel (Wattyl) and you by law is limited at the election of Hempel (Wattyl) to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

All brands and product names are registered trademarks of Hempel (Wattyl) Australia Pty Ltd ABN 40 000 035 914 and Hempel (Wattyl) New Zealand Pty Ltd 942 904 073 3692.

Calsil® is a registered trademark of Boral Resources (Vic) Pty Ltd.

Exotec® is a registered trademark of James Hardie International Finance B.V.

WATTYL ASSIST: Ph: 132 101 (AUSTRALIA)  
Ph: 0800 825 7727 (NEW ZEALAND)

# Safety Data Sheet

## GRANOSITE GRANOROLL-ON MEDIUM WHITE

Conforms to Model Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals - Australia

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : GRANOSITE GRANOROLL-ON MEDIUM WHITE  
Product identity : 861101  
Product type : Paint or paint related material

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : buildings  
Identified uses : Consumer applications, Professional applications, Used by spraying.

#### 1.3 Details of the supplier of the safety data sheet

Company details : Hempel (Wattyl) Australia Pty Ltd.  
Level 3, 2 Burbank Place  
Norwest, , New South Wales 2153  
Australia  
Tel: +(61) 288673333  
Email: wattyl@wattyl.com.au  
Date of Preparation : 2 May 2024  
Date of previous issue 12 April 2024.

#### 1.4 Emergency telephone number

Emergency telephone number (with hours of operation)  
  
Poisons Information Centre.  
Tel.: 13 11 26 (24 hour)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### GHS Classification

SKIN SENSITISATION - Category 1  
REPRODUCTIVE TOXICITY - Category 1

#### 2.2 Label elements

Hazard pictograms :



Signal word : DANGER

Hazard statements : H317 - May cause an allergic skin reaction.  
H360 - May damage fertility or the unborn child.

Precautionary statements :

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand.  
Prevention : Obtain special instructions before use. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Avoid breathing vapour.  
Response : IF exposed or concerned: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.  
Storage : Store locked up.  
Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.  
Supplemental label elements : Not applicable.

#### 2.3 Other hazards

Other hazards which do not result in classification : None known.

# Safety Data Sheet

## GRANOSITE GRANOROLL-ON MEDIUM WHITE

### SECTION 3: Composition/information on ingredients

| Product/ingredient name      | Identifiers | %    |
|------------------------------|-------------|------|
| dibutyl phthalate            | 84-74-2     | ≤1   |
| 2-methylisothiazol-3(2H)-one | 2682-20-4   | ≤0.1 |

Occupational exposure limits, if available, are listed in Section 8.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

|                              |                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General :                    | In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.<br>If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).                                                                                                                                     |
| Eye contact :                | Check for and remove any contact lenses. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. In all cases of doubt, or when symptoms persist, seek medical attention.                                                                                                                                                                                  |
| Inhalation :                 | Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately.                                                                |
| Skin contact :               | Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.                                                                                                                                                                                                                                                |
| Ingestion :                  | If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.                                                                                                                                          |
| Protection of first-aiders : | No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

|                |                                                   |
|----------------|---------------------------------------------------|
| Eye contact :  | No known significant effects or critical hazards. |
| Inhalation :   | No known significant effects or critical hazards. |
| Skin contact : | May cause an allergic skin reaction.              |
| Ingestion :    | No known significant effects or critical hazards. |

##### Over-exposure signs/symptoms

|                |                                                                                                                                                      |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye contact :  | No specific data.                                                                                                                                    |
| Inhalation :   | Adverse symptoms may include the following:<br>reduced foetal weight<br>increase in foetal deaths<br>skeletal malformations                          |
| Skin contact : | Adverse symptoms may include the following:<br>irritation<br>redness<br>reduced foetal weight<br>increase in foetal deaths<br>skeletal malformations |
| Ingestion :    | Adverse symptoms may include the following:<br>reduced foetal weight<br>increase in foetal deaths<br>skeletal malformations                          |

#### 4.3 Indication of any immediate medical attention and special treatment needed

|                       |                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| Notes to physician :  | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments : | No specific treatment.                                                                                                    |

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Extinguishing media : Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray.  
Not to be used : waterjet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials: carbon oxides metal oxide/oxides

#### 5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Hazchem code : ●3Z

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

#### 6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilt product.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

# Safety Data Sheet

## GRANOSITE GRANOROLL-ON MEDIUM WHITE

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

| Product/ingredient name                           | Exposure limit values                                                                                                                                   |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| dibutyl phthalate<br>2-methylisothiazol-3(2H)-one | <b>Safe Work Australia (Australia, 10/2022).</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours.<br><b>DFG MAC-values list (Germany, 7/2023). Skin sensitizer.</b> |

#### Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### 8.2 Exposure controls

##### Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

##### Individual protection measures

General :

Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.



Hygiene measures :

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.

Eye/face protection :

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Hand protection :

Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.

Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:

Recommended: Silver Shield / Barrier / 4H gloves, nitrile rubber (>0.3 mm), neoprene rubber (>0.1 mm), butyl rubber (>0.5 mm), natural rubber (latex) (>0.4 mm), polyvinyl chloride (PVC), Viton®, nitrile rubber (>0.1 mm), butyl rubber (>0.3 mm)

Short term exposure: polyvinyl alcohol (PVA)

Body protection :

Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.

Respiratory protection :

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear appropriate respirator when ventilation is inadequate. Be sure to use approved/certified respirator or equivalent. It is not possible to specify precise filter type, since the actual work situation is unknown. Supplier of respirators should be contacted in order to find the appropriate filter.

##### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

|                                                |                                                                                                  |
|------------------------------------------------|--------------------------------------------------------------------------------------------------|
| Physical state :                               | Liquid.                                                                                          |
| Odour :                                        | Non-characteristic.                                                                              |
| pH :                                           | Testing not relevant or not possible due to nature of the product.                               |
| Melting point/freezing point :                 | 1610°C This is based on data for the following ingredient: quartz (chrySTALLINE, non respirable) |
| Boiling point/boiling range :                  | Testing not relevant or not possible due to nature of the product.                               |
| Flash point :                                  | Closed cup: 100°C (212°F)                                                                        |
| Evaporation rate :                             | Testing not relevant or not possible due to nature of the product.                               |
| Flammability :                                 | Not available.                                                                                   |
| Lower and upper explosive (flammable) limits : | No specific data.                                                                                |
| Vapour pressure :                              | Testing not relevant or not possible due to nature of the product.                               |
| Vapour density :                               | Testing not relevant or not possible due to nature of the product.                               |
| Relative density :                             | 1.75 g/cm <sup>3</sup>                                                                           |
| Partition coefficient (LogKow) :               | Testing not relevant or not possible due to nature of the product.                               |
| Auto-ignition temperature :                    | Testing not relevant or not possible due to nature of the product.                               |
| Decomposition temperature :                    | Testing not relevant or not possible due to nature of the product.                               |
| Viscosity :                                    | Testing not relevant or not possible due to nature of the product.                               |
| Explosive properties :                         | Testing not relevant or not possible due to nature of the product.                               |
| Oxidising properties :                         | Testing not relevant or not possible due to nature of the product.                               |

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

The product is stable.

#### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4 Conditions to avoid

No specific data.

#### 10.5 Incompatible materials

Reactive or incompatible with the following materials: acids.

#### 10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides metal oxide/oxides

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

No known significant effects or critical hazards.

##### Acute toxicity

| Product/ingredient name      | Result                          | Species      | Dose         | Exposure |
|------------------------------|---------------------------------|--------------|--------------|----------|
| dibutyl phthalate            | LC50 Inhalation Dusts and mists | Rat          | >15.68 mg/l  | 4 hours  |
|                              | LD50 Dermal                     | Rabbit       | >20000 mg/kg | -        |
| 2-methylisothiazol-3(2H)-one | LD50 Oral                       | Rat          | 7499 mg/kg   | -        |
|                              | LC50 Inhalation Dusts and mists | Rat          | 0.11 mg/l    | 4 hours  |
|                              | LD50 Dermal                     | Rat          | 242 mg/kg    | -        |
|                              | LD50 Oral                       | Rat - Female | 183 mg/kg    | -        |
|                              |                                 |              |              |          |

# Safety Data Sheet

## GRANOSITE GRANOROLL-ON MEDIUM WHITE

### SECTION 11: Toxicological information

#### Acute toxicity estimates

| Route                                             | ATE value |
|---------------------------------------------------|-----------|
| No known significant effects or critical hazards. |           |

#### Irritation/Corrosion

| Product/ingredient name      | Result                   | Species | Score | Exposure |
|------------------------------|--------------------------|---------|-------|----------|
| 2-methylisothiazol-3(2H)-one | Skin - Moderate irritant | Rabbit  | -     | -        |

#### Sensitiser

| Product/ingredient name      | Route of exposure | Species    | Result      |
|------------------------------|-------------------|------------|-------------|
| 2-methylisothiazol-3(2H)-one | skin              | Guinea pig | Sensitising |

#### Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|----------|-------------------|---------------|
| Not available.          |          |                   |               |

#### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|----------|-------------------|---------------|
| Not available.          |          |                   |               |

#### Aspiration hazard

| Product/ingredient name | Result |
|-------------------------|--------|
| Not available.          |        |

#### Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

#### Potential chronic health effects

Other information : No additional known significant effects or critical hazards.

### SECTION 12: Ecological information

#### 12.1 Toxicity

Do not allow to enter drains or watercourses. Very toxic to aquatic life.

| Product/ingredient name      | Result                            | Species                                                                           | Exposure |
|------------------------------|-----------------------------------|-----------------------------------------------------------------------------------|----------|
| dibutyl phthalate            | Acute EC50 3.4 µg/l Marine water  | Algae - Dinoflagellate - Gymnodinium breve                                        | 96 hours |
|                              | Acute EC50 2990 µg/l Fresh water  | Daphnia - Water flea - Daphnia magna                                              | 48 hours |
|                              | Acute LC50 480 µg/l Fresh water   | Fish - Bluegill - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
|                              | Chronic NOEC 210 µg/l Fresh water | Algae - Green algae - Pseudokirchneriella subcapitata                             | 96 hours |
|                              | Chronic NOEC 500 µg/l Fresh water | Daphnia - Water flea - Daphnia magna                                              | 21 days  |
| 2-methylisothiazol-3(2H)-one | Chronic NOEC 25 µg/l Fresh water  | Fish - Zebra danio - Danio rerio - Embryo                                         | 5 weeks  |
|                              | Acute EC50 0.158 mg/l             | Algae                                                                             | 72 hours |
|                              | Acute EC50 0.063 mg/l             | Algae                                                                             | 96 hours |
|                              | Acute EC50 0.87 mg/l              | Daphnia                                                                           | 48 hours |
|                              | Acute LC50 0.056 ppm Marine water | Crustaceans - Calanoid copepod - Acartia tonsa                                    | 48 hours |
|                              | Acute LC50 4.77 mg/l              | Fish                                                                              | 96 hours |

#### 12.2 Persistence and degradability

| Product/ingredient name      | Test | Result                   | Dose | Inoculum |
|------------------------------|------|--------------------------|------|----------|
| 2-methylisothiazol-3(2H)-one | -    | 98 % - Readily - 48 days | -    | -        |

#### 12.3 Bioaccumulative potential

# Safety Data Sheet

## GRANOSITE GRANOROLL-ON MEDIUM WHITE

### SECTION 12: Ecological information

| Product/ingredient name      | LogP <sub>ow</sub> | BCF    | Potential |
|------------------------------|--------------------|--------|-----------|
| dibutyl phthalate            | 4.46               | 165.96 | low       |
| 2-methylisothiazol-3(2H)-one | -0.32              | 3.16   | low       |

#### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : No known data available in our database.

Mobility : No known data available in our database.

#### Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

The generation of waste should be avoided or minimised wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

#### Packaging

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

### SECTION 14: Transport information

Transport may take place according to national regulation NZS for transport by road and train, IMDG for transport by sea, IATA for transport by air.

|                   | 14.1<br>UN no. | 14.2<br>Proper shipping name                                             | 14.3<br>Transport hazard class(es)                                                                                                                                           | 14.4<br>PG* | 14.5<br>Env* | Additional information                                                                                                                                                                                                                                                                                                                    |
|-------------------|----------------|--------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>ADG Class</b>  | UN3082         | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (dibutyl phthalate)  | 9<br>  | III         | Yes.         | The product is not regulated as a dangerous good when transported by road or rail in either an IBC, or in other container types if ≤500 kg. This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. |
| <b>IMDG Class</b> | UN3082         | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.. (dibutyl phthalate) | 9<br>  | III         | Yes.         | This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. <b>Emergency schedules</b> F-A, S-F                                                                                                         |
| <b>IATA Class</b> | UN3082         | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (dibutyl phthalate)  | 9<br>  | III         | Yes.         | This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.                                                                                                                                                  |

PG\* : Packing group

Env.\* : Environmental hazards

#### 14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Transport in bulk according to IMO instruments

# Safety Data Sheet

## GRANOSITE GRANOROLL-ON MEDIUM WHITE

### SECTION 14: Transport information

Not applicable.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

| Ingredient name                       | Schedule                                                                                    |
|---------------------------------------|---------------------------------------------------------------------------------------------|
| quartz (chrySTALLine, non respirable) | Restricted hazardous chemical [For abrasive blasting at a concentration of greater than 1%] |

### SECTION 16: Other information

▀ Indicates information that has changed from previously issued version.

| Classification                                                        | Justification                            |
|-----------------------------------------------------------------------|------------------------------------------|
| SKIN SENSITISATION - Category 1<br>REPRODUCTIVE TOXICITY - Category 1 | Calculation method<br>Calculation method |

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

TEXTURE SOLUTIONS  
GRANOROLL-ON MEDIUM

RESOURCE CODE 861101

SEPTEMBER 2021

PAGE 1 OF 3



## Description &amp; Uses

GranoRoll-On Medium is an acrylic, high performance coating applied by black texture roller or 18mm pile roller to achieve a medium or low profiled texture. GranoRoll-On Medium is well suited for high traffic areas as it exhibits extremely good abrasion and impact resistance. GranoRoll-On Medium may be left matt or overcoated with GranoShield Matt, GranoImpact or GranoSkin Membrane.

## Features &amp; Benefits

- Suitable for high traffic areas
- Exhibits extremely good abrasion and impact resistance

## Colours &amp; Gloss

Base may be tinted as required. Tint using Ecotint® to Wattyl Colour Designer® range of colours or other competitor colours.

Matt.  
Matt when overcoated with GranoShield Matt (G2.27).  
Low Sheen when overcoated with GranoImpact (G2.01).  
Satin when overcoated with GranoSkin Membrane (G2.14).

For exterior application, it is recommended that the light-fastness of the chosen colour be confirmed before ordering.

## Properties &amp; Performance Guide

|                    |                                                                                                                            |
|--------------------|----------------------------------------------------------------------------------------------------------------------------|
| Dry & Recoat Times | Surface Dry - 4 hours                                                                                                      |
|                    | Recoat - 24 hours                                                                                                          |
|                    | Hard Dry - 7 days                                                                                                          |
|                    | Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity. |
| Density            | 1.7 Kg/L.                                                                                                                  |
| Consistency        | Thick, creamy paste.                                                                                                       |
| Texture            | Medium or high profile texture.                                                                                            |
| Coverage per Coat  | 0.6 L/M <sup>2</sup> (1.6 M <sup>2</sup> /L).                                                                              |
| Wet Film Thickness | 600 microns (approx).                                                                                                      |
| Dry Film Thickness | 380 microns (approx).                                                                                                      |
| Moisture Control   | Excellent, however, the coating should not be subject to hydrostatic pressure.                                             |

TEXTURE SOLUTIONS  
GRANOROLL-ON MEDIUM

RESOURCE CODE 861101

SEPTEMBER 2021

PAGE 2 OF 3

## Properties &amp; Performance Guide...Continued

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Abrasion Resistance              | Excellent.                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Thinning                         | Not required but if desired thin sparingly with water.                                                                                                                                                                                                                                                                                                                                                                                   |
| Clean Up                         | Clean up with cold water away from drains.<br><b>Protect Our Environment:</b> Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first. |
| VOC (Volatile Organic Compounds) | VOC < 10g/L.                                                                                                                                                                                                                                                                                                                                                                                                                             |

## Recommended Substrate Conditions &amp; Preparation

Surfaces are to be suitably prepared in accordance with proper trade practices.

GranoRoll-On Medium may be applied to off-form concrete Class 2 (AS 1510) or equivalent, cement rendered fair-faced flush-jointed concrete block and brickwork (common, clay, concrete, Calsil®, and extruded), CFC, tilt-up and pre-cast concrete, and paper-faced plasterboard. Make-good of the substrate is necessary if substrate imperfections are to be eliminated. Please refer to Technical Data Sheets for GranoRender Sponge Fine Finish (G1.17), GranoRender Coarse (G1.18), GranoRender PM Medium (G1.25), GranoPatch Smooth (G1.04), or GranoPatch Spackle (G1.05).

Surface preparation is the responsibility of the Builder, Renovator or Main Contractor and the Applicator. To achieve the indicated performance, application must be carried out according to Wattyl's recommendations.

Ensure the surface is clean and dry. All substrates must be free of dirt, dust, grease, oil, mould release agents, bondbreakers and any other contaminants that may interfere with adhesion.

Fresh cementitious substrates should be left for 14-28 days before coating. There must be less than 15% moisture content in the surface at the time of coating to ensure optimum coating performance.

The substrate must not be subjected to continual wetting, ponding water or hydrostatic pressure.

For specific substrate preparation, see relevant specification sheets.

## Application Guide

Stir contents thoroughly with a power stirrer before use.

GranoRoll-On Medium is applied in 1 coat by medium black texture roller or 18mm pile roller to a correctly prepared and primed surface.

NOTE: The texture achieved will vary depending on the supplier of the texture roller.

If GranoRoll-On Medium is used as the final coat in a 'matt' system, consistency of colour between different drums and/or batches cannot be guaranteed. Topcoating with GranoShield Matt, GranoImpact or GranoSkin Membrane is recommended for consistency of colour, system longevity and ease of maintenance.

Freshly applied material must be protected from frosts and rain for a minimum of forty-eight (48) hours.

Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C or when humidity is very high. The temperature must not fall below 10°C during the drying process.

In exterior application avoid painting when dew or rain is likely.

TEXTURE SOLUTIONS  
GRANOROLL-ON MEDIUM

RESOURCE CODE 861101

SEPTEMBER 2021

PAGE 3 OF 3

## Additional Data

Available in 15 litre containers.  
Not suitable for horizontal roofs, ponds etc., or walk-on surfaces.  
Tinted paint is non-refundable, so choose your colours carefully.  
If using more than one container for the final coat, check that the colour is correct in all containers and mix the paint together to ensure colour consistency before starting.  
Leave 7 days after application of final coat before washing. Wash using a sponge or soft cloth with warm water and mild detergent. Avoid harsh scrubbing and strong household cleaners.  
Containers must be secured and stored upright during transit.  
Containers must not be exposed to excessive heat or cold.  
Storage must be under cover, away from direct heat, freezing and moisture, in well-sealed containers.  
It is recommended that application be carried out by a skilled applicator, who is totally conversant with the Granosite products and systems, to validate full material warranty conditions.  
The use of proprietary additives other than those manufactured by Wattyl is not recommended.  
Do not use for any other purpose other than as specified in our literature.

## Safety Data

|                               |                                                                                                                                                                                                                                                                                                                                                                                                        |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>First Aid Instructions</b> | For advice, contact the Poisons Information Centre on 131 126 (Australia), 0800 764 766 (New Zealand), or a doctor.<br>If swallowed, do not induce vomiting. Give a glass of water to drink.<br>If in eyes, wash out immediately with water.<br>If inhaled remove from contaminated area to fresh air.<br>If skin contact occurs, remove contaminated clothing and flush contaminated skin with water. |
| <b>Safety Directions</b>      | Keep out of reach of children.<br>Avoid contact with skin and eyes.<br>Ensure adequate ventilation during use.<br>Avoid prolonged breathing of vapour.<br>Wash hands thoroughly after use.                                                                                                                                                                                                             |
| <b>Further Information</b>    | For the latest information refer to the Safety Data Sheet available on our websites.<br>Australia: <a href="http://www.wattyl.com.au">www.wattyl.com.au</a> or contact Wattyl Assist on 132 101.<br>New Zealand: <a href="http://www.wattyl.co.nz">www.wattyl.co.nz</a> or contact Wattyl Assist on 0800 825 7727.                                                                                     |

1. This information is provided with respect to the listed Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand products. Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand, hereon referred to as "Hempel (Wattyl)," recommends that:

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Hempel (Wattyl); (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in the TDS was prepared using information gathered during product development. While Hempel (Wattyl) endeavour to update this information and maintain the accuracy of its contents, Hempel (Wattyl) cannot guarantee that the information is wholly comprehensive.

3. Hempel (Wattyl) recommend that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest office of Hempel (Wattyl).

4. To the full extent permitted by law, the liability of Hempel (Wattyl) for breach of a condition or warranty implied into the contract for sale between Hempel (Wattyl) and you by law is limited at the election of Hempel (Wattyl) to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

All brands and product names are registered trademarks of Hempel (Wattyl) Australia Pty Ltd ABN 40 000 035 914 and Hempel (Wattyl) New Zealand Pty Ltd 942 904 073 3692.

Calsil® is a registered trademark of Boral Resources (Vic) Pty Ltd.

WATTYL ASSIST: Ph: 132 101 (AUSTRALIA)  
Ph: 0800 825 7727 (NEW ZEALAND)

Conforms to Model Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals - Australia

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : WATTYL GRANOSITE GRANOIMPACT WHITE  
Product identity : 860101  
Product type : Paint or paint related material

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : buildings  
Identified uses : Consumer applications, Professional applications, Used by spraying.

#### 1.3 Details of the supplier of the safety data sheet

Company details : Hempel (Wattyl) Australia Pty Ltd.  
Level 3, 2 Burbank Place  
Norwest, , New South Wales 2153  
Australia  
Tel: +(61) 288673333  
Email: wattyl@wattyl.com.au  
Date of Preparation : 5 December 2024  
Date of previous issue : 2 May 2024.

#### 1.4 Emergency telephone number

Emergency telephone number (with hours of operation)  
  
Poisons Information Centre.  
Tel.: 13 11 26 (24 hour)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### GHS Classification

 SKIN SENSITISATION - Category 1

#### 2.2 Label elements

Hazard pictograms :



Signal word :  WARNING

Hazard statements :  H317 - May cause an allergic skin reaction.

Precautionary statements :

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand.  
Prevention :  P273 - Wear protective gloves. Avoid breathing vapour.  
Response :  P330+P361+P353 - IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.  
Disposal :  P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.  
Supplemental label elements : Not applicable.

#### 2.3 Other hazards

Other hazards which do not result in classification : None known.

### SECTION 3: Composition/information on ingredients

| Product/ingredient name                                                                                                                                                            | Identifiers                                        | %                |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|------------------|
|  (2-butoxyethoxy)ethanol<br>Kerosine (petroleum), hydrosulfurized<br>2-methylisothiazol-3(2H)-one | CAS: 112-34-5<br>CAS: 64742-81-0<br>CAS: 2682-20-4 | ≤3<br>≤3<br>≤0.1 |

Occupational exposure limits, if available, are listed in Section 8.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

|                              |                                                                                                                                                                                                                                                                                                                                    |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General :                    | In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.<br>If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).                                                                      |
| Eye contact :                | Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.                                                                                                                           |
| Inhalation :                 | Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. |
| Skin contact :               |  Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. Remove contaminated clothing and shoes.                                                                                               |
| Ingestion :                  | If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.                                                                           |
| Protection of first-aiders : | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.                                                                      |

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

|                |                                                   |
|----------------|---------------------------------------------------|
| Eye contact :  | No known significant effects or critical hazards. |
| Inhalation :   | No known significant effects or critical hazards. |
| Skin contact : | May cause an allergic skin reaction.              |
| Ingestion :    | No known significant effects or critical hazards. |

##### Over-exposure signs/symptoms

|                |                                                                      |
|----------------|----------------------------------------------------------------------|
| Eye contact :  | No specific data.                                                    |
| Inhalation :   | No specific data.                                                    |
| Skin contact : | Adverse symptoms may include the following:<br>irritation<br>redness |
| Ingestion :    | No specific data.                                                    |

#### 4.3 Indication of any immediate medical attention and special treatment needed

|                       |                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| Notes to physician :  | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments : | No specific treatment.                                                                                                    |

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Extinguishing media : Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray.  
Not to be used : waterjet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture :  In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials: carbon oxides metal oxide/oxides

#### 5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Hazchem code : -

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

#### 6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilt product.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

| Product/ingredient name                                                                                        | Exposure limit values                                                                                                                                                                                                                                                                                                                       |
|----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>2-butoxyethoxy)ethanol</p> <p>Kerosine (petroleum), hydrosulfurized</p> <p>2-methylisothiazol-3(2H)-one</p> | <p><b>ACGIH TLV (United States, 1/2024)</b><br/>TWA 8 hours: 10 ppm. Form: Inhalable fraction and vapor.</p> <p><b>ACGIH TLV (United States, 1/2024) [Kerosene] A3.</b> Absorbed through skin.<br/>TWA 8 hours: 200 mg/m<sup>3</sup> (as total hydrocarbon vapor).</p> <p><b>DFG MAC-values list (Germany, 7/2023)</b> Skin sensitizer.</p> |

#### Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### 8.2 Exposure controls

##### Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

##### Individual protection measures

General :

Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.



Hygiene measures :

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.

Eye/face protection :

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Hand protection :

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.

Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:

Recommended: Silver Shield / Barrier / 4H gloves, nitrile rubber (>0.3 mm), neoprene rubber (>0.1 mm), butyl rubber (>0.5 mm), natural rubber (latex) (>0.4 mm), polyvinyl chloride (PVC), Viton®, nitrile rubber (>0.1 mm), butyl rubber (>0.3 mm)

Short term exposure: polyvinyl alcohol (PVA)

Body protection :

Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.

Respiratory protection :

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear appropriate respirator when ventilation is inadequate. Be sure to use approved/certified respirator or equivalent. It is not possible to specify precise filter type, since the actual work situation is unknown. Supplier of respirators should be contacted in order to find the appropriate filter.

##### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

|                                |                                                                                                                        |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Physical state :               | Liquid.                                                                                                                |
| Odour :                        | Non-characteristic.                                                                                                    |
| pH :                           | 7- 9                                                                                                                   |
| Melting point/freezing point : | Testing not relevant or not possible due to nature of the product.                                                     |
| Boiling point/boiling range :  | Testing not relevant or not possible due to nature of the product.                                                     |
| Flash point :                  | Closed cup: 98°C (208.4°F)                                                                                             |
| Evaporation rate :             | Testing not relevant or not possible due to nature of the product.                                                     |
| Flammability :                 | Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. |

Vapour pressure :

|                                                                                         | Vapour Pressure at 20°C |     |        | Vapour pressure at 50°C |     |        |
|-----------------------------------------------------------------------------------------|-------------------------|-----|--------|-------------------------|-----|--------|
| Ingredient name                                                                         | mm Hg                   | kPa | Method | mm Hg                   | kPa | Method |
|  water | 17.5                    | 2.3 |        |                         |     |        |

|                                  |                                                                    |
|----------------------------------|--------------------------------------------------------------------|
| Vapour density :                 | Not available.                                                     |
| Specific gravity :               | 1.37 g/cm <sup>3</sup>                                             |
| Partition coefficient (LogKow) : | Testing not relevant or not possible due to nature of the product. |
| Auto-ignition temperature :      | Not available.                                                     |
| Decomposition temperature :      | Testing not relevant or not possible due to nature of the product. |
| Viscosity :                      | Testing not relevant or not possible due to nature of the product. |
| Explosive properties :           | Testing not relevant or not possible due to nature of the product. |
| Oxidising properties :           | Testing not relevant or not possible due to nature of the product. |

#### 9.2 Other information

|                          |                                          |
|--------------------------|------------------------------------------|
| Solvent(s) % by weight : | Weighted average: 5 %                    |
| Water % by weight :      | Weighted average: 33 %                   |
| VOC content :            | 64.2 g/l                                 |
| TOC Content :            | Weighted average: 48 g/l                 |
| Solvent Gas :            | Weighted average: 0.01 m <sup>3</sup> /l |

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

The product is stable.

#### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4 Conditions to avoid

No specific data.

#### 10.5 Incompatible materials

Reactive or incompatible with the following materials: oxidising materials and acids.  
Slightly reactive or incompatible with the following materials: reducing materials.

#### 10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:  
Decomposition products may include the following materials: carbon oxides metal oxide/oxides

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

#### Acute toxicity

| Product/ingredient name                                                                                   | Result                                  | Dose / Exposure     | Effects                                                                                         |
|-----------------------------------------------------------------------------------------------------------|-----------------------------------------|---------------------|-------------------------------------------------------------------------------------------------|
|  (2-butoxyethoxy)ethanol | Rat - Oral - LD50                       | 4500 mg/kg          | Toxic effects: Behavioral - Tetany Lung, Thorax, or Respiration - Dyspnea Liver - Other changes |
| Kerosine (petroleum), hydrodesulfurized<br>2-methylisothiazol-3(2H)-one                                   | Rabbit - Dermal - LD50                  | 2700 mg/kg          |                                                                                                 |
|                                                                                                           | Rat - Oral - LD50                       | >5000 mg/kg         |                                                                                                 |
|                                                                                                           | Rat - Female - Oral - LD50              | 183 mg/kg           |                                                                                                 |
|                                                                                                           | Rat - Dermal - LD50                     | 242 mg/kg           |                                                                                                 |
|                                                                                                           | Rat - Inhalation - LC50 Dusts and mists | 0.11 mg/l [4 hours] |                                                                                                 |

#### Acute toxicity estimates

| Route                                             | ATE value |
|---------------------------------------------------|-----------|
| No known significant effects or critical hazards. |           |

#### Irritation/Corrosion

| Product/ingredient name                                                                                     | Result                            | Species                                      | Exposure                                     |
|-------------------------------------------------------------------------------------------------------------|-----------------------------------|----------------------------------------------|----------------------------------------------|
|  (2-butoxyethoxy)ethanol | Rabbit - Eyes - Severe irritant   | Duration of treatment/<br>exposure: 24 hours | Amount/concentration applied: 20 milligrams  |
| Kerosine (petroleum), hydrodesulfurized<br>2-methylisothiazol-3(2H)-one                                     | Rabbit - Skin - Moderate irritant |                                              | Amount/concentration applied: 500 milligrams |
|                                                                                                             | Rabbit - Skin - Moderate irritant |                                              |                                              |

#### Sensitiser

| Product/ingredient name                                                                                        | Species - Route of exposure | Result              |
|----------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------|
|  methylisothiazol-3(2H)-one | Guinea pig - skin           | Result: Sensitising |

#### Mutagenic effects

No known data available in our database.

#### Carcinogenicity

No known data available in our database.

#### Reproductive toxicity

No known data available in our database.

#### Specific target organ toxicity (single exposure)

| Product/ingredient name                                                                                                     | Category   | Route of exposure | Target organs    |
|-----------------------------------------------------------------------------------------------------------------------------|------------|-------------------|------------------|
|  Kerosine (petroleum), hydrodesulfurized | Category 3 |                   | Narcotic effects |

#### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|----------|-------------------|---------------|
| Not available.          |          |                   |               |

#### Aspiration hazard

| Product/ingredient name                 | Result                         |
|-----------------------------------------|--------------------------------|
| Kerosine (petroleum), hydrodesulfurized | ASPIRATION HAZARD - Category 1 |

#### Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

### SECTION 11: Toxicological information

#### Potential chronic health effects

No known significant effects or critical hazards.

Other information : No additional known significant effects or critical hazards.

### SECTION 12: Ecological information

#### 12.1 Toxicity

Do not allow to enter drains or watercourses. Very toxic to aquatic life with long lasting effects.

| Product/ingredient name      | Result                      | Species                                               | Exposure              |
|------------------------------|-----------------------------|-------------------------------------------------------|-----------------------|
| 2-(2-butoxyethoxy)ethanol    | Acute - EC50                | Algae                                                 | 100 mg/l [96 hours]   |
| 2-methylisothiazol-3(2H)-one | Acute - LC50                | Fish                                                  | 1300 mg/l [96 hours]  |
|                              | Acute - LC50 - Marine water | Crustaceans - Calanoid copepod - <i>Acartia tonsa</i> | 0.056 ppm [48 hours]  |
|                              | Acute - LC50                | Fish                                                  | 4.77 mg/l [96 hours]  |
|                              | Acute - EC50                | Algae                                                 | 0.158 mg/l [72 hours] |
|                              | Acute - EC50                | Algae                                                 | 0.063 mg/l [96 hours] |

#### 12.2 Persistence and degradability

| Product/ingredient name      | Test | Result                  |
|------------------------------|------|-------------------------|
| 2-methylisothiazol-3(2H)-one |      | 98% [48 days] - Readily |

#### 12.3 Bioaccumulative potential

| Product/ingredient name      | LogP <sub>ow</sub> | BCF  | Potential |
|------------------------------|--------------------|------|-----------|
| 2-(2-butoxyethoxy)ethanol    | 1                  | -    | Low       |
| 2-methylisothiazol-3(2H)-one | -0.32              | 3.16 | Low       |

#### 12.4 Mobility in soil

| Product/ingredient name      | logK <sub>oc</sub> | K <sub>oc</sub> |
|------------------------------|--------------------|-----------------|
| 2-(2-butoxyethoxy)ethanol    | 1.56               | 36.5981         |
| diuron (ISO)                 | 2.4                | 250.231         |
| 2-octyl-2H-isothiazol-3-one  | 2.85               | 706.605         |
| 1,2-benzisothiazol-3(2H)-one | 1.86               | 73.142          |
| 2-methylisothiazol-3(2H)-one | 1.74               | 54.9187         |

Mobility : No known data available in our database.

#### Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

The generation of waste should be avoided or minimised wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

#### Packaging

The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

### SECTION 14: Transport information

Transport may take place according to national regulation ADG for transport by road and train, IMDG for transport by sea, IATA for transport by air.

### SECTION 14: Transport information

|                   | 14.1<br>UN no. | 14.2<br>Proper shipping name | 14.3<br>Transport hazard class(es) | 14.4<br>PG* | 14.5<br>Env* | Additional information |
|-------------------|----------------|------------------------------|------------------------------------|-------------|--------------|------------------------|
| <b>ADG Class</b>  | Not regulated. |                              | -                                  | -           | No.          | -                      |
| <b>IMDG Class</b> | Not regulated. |                              | -                                  | -           | No.          | -                      |
| <b>IATA Class</b> | Not regulated. |                              | -                                  | -           | No.          | -                      |

PG\* : Packing group

Env.\* : Environmental hazards

#### 14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Transport in bulk according to IMO instruments

Not applicable.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

| Ingredient name     | Schedule |
|---------------------|----------|
| No listed substance |          |

### SECTION 16: Other information

Indicates information that has changed from previously issued version.

| Classification                  | Justification      |
|---------------------------------|--------------------|
| SKIN SENSITISATION - Category 1 | Calculation method |

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

TEXTURE SOLUTIONS  
GRANOIMPACT

RESOURCE CODE 86010-Line

NOVEMBER 2024

PAGE 1 OF 4



## Description &amp; Uses

GranolImpact is a pure acrylic, high performance coating able to applied in a variety of styles by roller or spray. As an acrylic membrane, the vapour permeability of GranolImpact is carefully controlled to form a barrier to external moisture, while allowing vapour in the substrate to escape. GranolImpact systems have good adhesion to a wide variety of substrates. GranolImpact also forms the final topcoat of many other Granosite systems, extending the performance and overall protection of the system applied. GranolImpact is water-based for applicator safety and ease of use.

## Features &amp; Benefits

- Good flexibility, elasticity and crack bridging
- Anti-carbonation coating system
- Excellent resistance to chloride ion diffusion
- Excellent resistance to dirt, mould and fungi
- Forms a barrier to external moisture while allowing vapour in the substrate to escape

## Colours &amp; Gloss

White, Light, Mid and Strong bases. Tint using Ecotint® to Wattyl Colour Designer® range of colours or other competitor colours.

Low Sheen.

For exterior application, it is recommended that the light-fastness of the chosen colour be confirmed before ordering.

## Environmental Data &amp; Certifications



Approved to Australia Paint Approval Scheme Specification APAS 0117/3.  
Australian Standard AS4548.3

TEXTURE SOLUTIONS  
GRANOIMPACT

RESOURCE CODE 86010-Line

NOVEMBER 2024

PAGE 2 OF 4

## Properties &amp; Performance Guide

|                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                      |                                               |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|-----------------------------------------------|
| Dry & Recoat Times               | Surface Dry - 4 hours<br>Recoat - 6 hours<br>Hard Dry - 7 days<br>Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.                                                                                                                                                                                                                                             |                                                      |                                               |
| Density                          | 1.38 Kg/L.                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                      |                                               |
| Consistency                      | Thick, creamy paste.                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                      |                                               |
| Texture                          | <b>Low Profile</b><br>(10-12mm pile roller)                                                                                                                                                                                                                                                                                                                                                                                              | <b>High Profile</b><br>(Medium black texture roller) | <b>Airless</b><br>(Airless Spray Gun)         |
| Coverage per 2-Coat System       | 0.35 L/M <sup>2</sup> (2.9M <sup>2</sup> /L).                                                                                                                                                                                                                                                                                                                                                                                            | 0.50 L/M <sup>2</sup> (2M <sup>2</sup> /L).          | 0.66 L/M <sup>2</sup> (1.5M <sup>2</sup> /L). |
| Wet Film Thickness               | 335 microns (approx).                                                                                                                                                                                                                                                                                                                                                                                                                    | 500 microns (approx).                                | 660 microns (approx).                         |
| Dry Film Thickness               | 160 microns (approx).                                                                                                                                                                                                                                                                                                                                                                                                                    | 240 microns (approx).                                | 320 microns (approx).                         |
| Moisture Control                 | Excellent, however, the coating should not be subject to hydrostatic pressure.                                                                                                                                                                                                                                                                                                                                                           |                                                      |                                               |
| Water Ponding                    | 50.5 – Excellent (mg of water passed after 50 hours at 25°C and 50% relative humidity).                                                                                                                                                                                                                                                                                                                                                  |                                                      |                                               |
| Water Transmission               | 7.0 gm/24 hours/m <sup>2</sup> (AS/NZS4548.5).                                                                                                                                                                                                                                                                                                                                                                                           |                                                      |                                               |
| Water Permeability               | Passed (AS 2904 Appendix G – 6 metre head of water).                                                                                                                                                                                                                                                                                                                                                                                     |                                                      |                                               |
| Vapour Permeability              | 12.6 gm/m <sup>2</sup> /24 hours (DIN 52615 (at 500um dry film build)).                                                                                                                                                                                                                                                                                                                                                                  |                                                      |                                               |
| Vapour Transmission              | 35.6 gm/m <sup>2</sup> /24 hours (AS/NZS4548.5), Sd 1.25m (AS/NZS4548.5).                                                                                                                                                                                                                                                                                                                                                                |                                                      |                                               |
| Carbon Dioxide Diffusion         | Rb 459.6m (Engelfried Method).                                                                                                                                                                                                                                                                                                                                                                                                           |                                                      |                                               |
| Chloride Ion Diffusion           | 1.3 x 10 <sup>-9</sup> cm <sup>2</sup> sec <sup>-1</sup> (Taywood in-house method).                                                                                                                                                                                                                                                                                                                                                      |                                                      |                                               |
| Abrasion Resistance              | 5,000 cycles – Film integrity excellent (AS 1580 459.1).                                                                                                                                                                                                                                                                                                                                                                                 |                                                      |                                               |
| Salt Spray                       | No effect (AS 2331.3.1).                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                      |                                               |
| Elongation                       | 524% (ASTM D-412 at 25°C).                                                                                                                                                                                                                                                                                                                                                                                                               |                                                      |                                               |
| Tensile Strength                 | 36.4 kg/cm <sup>2</sup> (ASTM D-412 at 25°C).                                                                                                                                                                                                                                                                                                                                                                                            |                                                      |                                               |
| Crack Bridging                   | 3.65 (Crack width bridged per unit dry film thickness).                                                                                                                                                                                                                                                                                                                                                                                  |                                                      |                                               |
| Dirt Pick-Up                     | 1 – on a scale of 0 – 5 where “0” is no dirt retained (AS 1580 481.1.4 12 months).                                                                                                                                                                                                                                                                                                                                                       |                                                      |                                               |
| Thinning                         | Not required but may be thinned with up to 10% water for cutting in and spray applications. Thinning rates for airless spray will vary according to the brand of equipment used.                                                                                                                                                                                                                                                         |                                                      |                                               |
| Clean Up                         | Clean up with cold water away from drains.<br><b>Protect Our Environment:</b> Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Check with your local council first. |                                                      |                                               |
| VOC (Volatile Organic Compounds) | VOC < 65g/L.                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                      |                                               |

TEXTURE SOLUTIONS  
GRANOIMPACT

RESOURCE CODE 86010-Line

NOVEMBER 2024

PAGE 3 OF 4

## Recommended Substrate Conditions &amp; Preparation

Surfaces are to be suitably prepared in accordance with proper trade practices.

GranoImpact may be applied to off-form concrete Class 2 (AS 1510) or equivalent, cement rendered fair-faced flush-jointed concrete block and brickwork (common, clay, concrete, Calsil®, and extruded), ExoTec®, CFC, tilt-up and pre-cast concrete, and paper-faced plasterboard. Make-good of the substrate is necessary if substrate imperfections are to be eliminated. Please refer to Technical Data Sheets (TDS) for GranoRender Sponge Fine Finish (G1.17), GranoRender Coarse (G1.18), GranoRender PM Medium (G1.25), GranoPatch Smooth (G1.04), GranoPatch Spackle (G1.05), GranoReady Render (G1.12) or GranoSponge Fine Acrylic (G1.21) where applicable. Additionally, in New Zealand, refer to the TDS's of Grano Adhesive Mortar (G1.06NZ), Grano Modified Render (G1.10NZ), Grano Sponge Finish (G1.25NZ), Grano Renovation Render (G1.17NZ) or Grano Lite-Weight Plaster® (G1.30NZ) where applicable. Surface preparation is the responsibility of the Builder, Renovator or Main Contractor and the Applicator. To achieve the indicated performance, application must be carried out according to Wattyl's recommendations.

Ensure the surface is clean and dry. All substrates must be free of dirt, dust, grease, oil, mould release agents, bondbreakers and any other contaminants that may interfere with adhesion.

Fresh cementitious substrates should be left for 14-28 days before coating. There must be less than 15% moisture content in the surface at the time of coating to ensure optimum coating performance.

The substrate must not be subjected to continual wetting, ponding water or hydrostatic pressure.

For specific substrate preparation, see relevant specification sheets.

## Application Guide

Stir contents thoroughly with a power stirrer before use.

Apply two full coats by roller or airless spray to a correctly prepared and primed surface.

**AIRLESS GUN SETTINGS:** Tip 519 or 521. Pressure Setting 2500-3000psi.

Freshly applied material must be protected from frosts and rain for a minimum of forty-eight (48) hours.

Application **should not** be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C or when humidity is very high. The temperature must not fall below 10°C during the drying process.

In exterior application avoid painting when dew or rain is likely.

## Additional Data

Available in 15 litre containers.

Not suitable for horizontal roofs, ponds etc., or walk-on surfaces.

Tinted paint is non-refundable, so choose your colours carefully.

If using more than one container for the final coat, check that the colour is correct in all containers and mix the paint together to ensure colour consistency before starting.

Leave 7 days after application of final coat before washing. Wash using a sponge or soft cloth with warm water and mild detergent. Avoid harsh scrubbing and strong household cleaners.

Containers must be secured and stored upright during transit.

Containers must not be exposed to excessive heat or cold.

Storage must be under cover, away from direct heat, freezing and moisture, in well-sealed containers.

It is recommended that application be carried out by a skilled applicator, who is totally conversant with the Granosite products and systems, to validate full material warranty conditions.

The use of proprietary additives other than those manufactured by Wattyl is not recommended.

Do not use for any other purpose other than as specified in our literature.

TEXTURE SOLUTIONS  
GRANOIMPACT

RESOURCE CODE 86010-Line

NOVEMBER 2024

PAGE 4 OF 4

## Safety Data

|                               |                                                                                                                                                                                                                                                                                                                                                                                                        |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>First Aid Instructions</b> | For advice, contact the Poisons Information Centre on 131 126 (Australia), 0800 764 766 (New Zealand), or a doctor.<br>If swallowed, do not induce vomiting. Give a glass of water to drink.<br>If in eyes, wash out immediately with water.<br>If inhaled remove from contaminated area to fresh air.<br>If skin contact occurs, remove contaminated clothing and flush contaminated skin with water. |
| <b>Safety Directions</b>      | Keep out of reach of children.<br>Avoid contact with skin and eyes.<br>Ensure adequate ventilation during use.<br>Avoid prolonged breathing of vapour.<br>Wash hands thoroughly after use.                                                                                                                                                                                                             |
| <b>Further Information</b>    | For the latest information refer to the Safety Data Sheet available on our websites.<br>Australia: <a href="http://www.wattyl.com.au">www.wattyl.com.au</a> or contact Wattyl Assist on 132 101.<br>New Zealand: <a href="http://www.wattyl.co.nz">www.wattyl.co.nz</a> or contact Wattyl Assist on 0800 825 7727.                                                                                     |

1. This information is provided with respect to the listed Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand products. Hempel (Wattyl) Australia and Hempel (Wattyl) New Zealand, hereon referred to as "Hempel (Wattyl)," recommends that:

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Hempel (Wattyl); (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in the TDS was prepared using information gathered during product development. While Hempel (Wattyl) endeavour to update this information and maintain the accuracy of its contents, Hempel (Wattyl) cannot guarantee that the information is wholly comprehensive.

3. Hempel (Wattyl) recommend that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest office of Hempel (Wattyl).

4. To the full extent permitted by law, the liability of Hempel (Wattyl) for breach of a condition or warranty implied into the contract for sale between Hempel (Wattyl) and you by law is limited at the election of Hempel (Wattyl) to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

All brands and product names are registered trademarks of Hempel (Wattyl) Australia Pty Ltd ABN 40 000 035 914 and Hempel (Wattyl) New Zealand Pty Ltd 942 904 073 3692.

Calsil® is a registered trademark of Boral Resources (Vic) Pty Ltd.

Exotec® is a registered trademark of James Hardie International Finance B.V.

WATTYL ASSIST: Ph: 132 101 (AUSTRALIA)  
Ph: 0800 825 7727 (NEW ZEALAND)